

# ISO 11393-1:2018 (E)

## Protective clothing for users of hand-held chainsaws — Part 1: Test rig for testing resistance to cutting by a chainsaw

---

### Contents

|         |  |
|---------|--|
|         | Foreword   |
|         | Introduction   |
| 1       | Scope  |
| 2       | Normative references   |
| 3       | Terms and definitions  |
| 4       | Principles   |
| 5       | Test rig   |
| 5.1     | General  |
| 5.2     | Power unit and connecting device                                     |
| 5.3     | Saw unit   |
| 5.3.1   | General  |
| 5.3.2   | Components of saw unit   |
| 5.3.2.1 | Guide bar  |
| 5.3.2.2 | Chain drive sprocket   |
| 5.3.2.3 | Moment of inertia of rotating parts                                  |
| 5.3.2.4 | Saw chain  |
| 5.3.2.5 | Lubrication system   |
| 5.3.3   | Release system   |
| 5.3.4   | Instrumentation  |
| 5.3.5   | Fixture for saw unit   |
| 5.4     | Calibration pad mount  |
| 5.5     | Calibration pad fixture device                                       |
| 6       | Calibration materials  |
| 7       | Calibration of the test rig  |
| 7.1     | General  |
| 7.2     | Starting up the rig  |
| 7.3     | Chain stopping time  |
| 7.4     | Measurement of chain speed   |
| 7.5     | Calibration with clogging material (pads)                            |
| 7.5.1   | Conditioning of the saw chain  |
| 7.5.2   | Attachment of calibration pad  |
| 7.5.3   | Cut test   |
| Annex A | (normative) Supplementary information on calibration pads            |
| Annex B | (normative) Testing of calibration pads at 19 m/s and 21 m/s         |
| Annex C | (informative) Method for checking the moment of inertia around pivot |