ISO 16073-9:2020 (E)

Wildland firefighting personal protective equipment — Requirements and test methods — Part 9: Firehoods

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 General design requirements

- 4.1 General
- 4.2 Firehood flexibility and facial opening
- 4.3 Yoke interface area
- 4.4 Sizing
- 4.5 Seam construction
- 4.6 Labels
- 4.7 Particulate protection (Optional)

5 Sampling and pre-treatment

- 5.1 Sampling
- 5.2 Pre-treatment by cleaning
- 5.3 Conditioning

6 Performance requirements

- 6.1 Flame resistance — Face ignition
- 6.2 Sewing thread thermal stability
- 6.3 Heat resistance
- 6.4 Heat transfer — Flame exposure
- 6.5 Heat transfer — Radiant exposure
- 6.6 Residual burst strength of material following radiant heat exposure
- 6.7 Seam burst strength
- 6.8 Dimensional change
- 6.9 Particulate protection
- 6.9.1 General
- 6.9.2 Test method 1
- 6.9.3 Test method 2
- 6.10 Water vapour resistance

7 Marking and labelling

- 7.1 General
- 7.2 Label durability and legibility
- 7.3 Compliance marking requirements

8 Information supplied by the manufacturer

Annex A (normative) Donning, doffing and shape retention test

Annex B (normative) Particulate test method 1

- B.1 Introduction
- B.2 Principle
- B.3 Test equipment
- B.4 Procedure

B.5 Calculation of the penetration

Annex C (normative) Particulate test method 2

C.1 Introduction
C.2 Apparatus and test parameters
C.3 Procedure
C.4 Calculation of the penetration

Annex D (informative) Particulate testing results

Page count: 16