

# ISO 22568-4:2021-12 (E)

## Foot and leg protectors - Requirements and test methods for footwear components - Part 4: Non-metallic perforation resistant inserts

---

| <b>Contents</b>   | <b>Page</b> |
|---|-------------|
| Foreword.....   | iv          |
| Introduction.....   | v           |
| <b>1 Scope.....</b>   | <b>1</b>    |
| <b>2 Normative references.....</b>  | <b>1</b>    |
| <b>3 Terms and definitions.....</b>   | <b>1</b>    |
| <b>4 Requirements for non-metallic perforation resistant inserts.....</b>                                       | <b>2</b>    |
| 4.1 General.....  | 2           |
| 4.2 Resistance to perforation.....  | 2           |
| 4.3 Flexing resistance.....   | 3           |
| 4.4 Stability against ageing and environmental influence.....   | 3           |
| 4.5 Electrical resistance.....  | 3           |
| <b>5 Test methods for the non-metallic perforation tests.....</b>   | <b>3</b>    |
| 5.1 Determination of perforation resistance.....  | 3           |
| 5.1.1 Method PL: with conical nail 4,5 mm diameter.....   | 3           |
| 5.1.2 Method PS: with conical nail 3,0 mm diameter.....   | 3           |
| 5.2 Determination of flexing resistance.....  | 3           |
| 5.2.1 Apparatus.....  | 3           |
| 5.2.2 Sampling.....   | 4           |
| 5.2.3 Test procedure.....   | 5           |
| 5.2.4 Results.....  | 5           |
| 5.2.5 Test report.....  | 5           |
| 5.3 Test methods for the assessment non-metallic perforation resistant inserts<br>in critical environment.....  | 6           |
| 5.3.1 Sampling.....   | 6           |
| 5.3.2 Effect of high temperature.....   | 6           |
| 5.3.3 Effect of acid sweat.....   | 6           |
| 5.3.4 Effect of alkali sweat.....   | 6           |
| 5.3.5 Effect of fuel oil.....   | 6           |
| 5.3.6 Results.....  | 6           |
| 5.3.7 Test report.....  | 6           |
| 5.4 Determination of the electrical resistance.....   | 7           |
| 5.4.1 Testing procedure.....  | 7           |
| 5.4.2 Test report.....  | 7           |
| <b>6 Marking.....</b>   | <b>8</b>    |
| <b>Annex A (normative) Method PL: perforation resistance with the conical nail 4,5 mm<br/>    diameter.....</b> | <b>9</b>    |
| <b>Annex B (normative) Method PS: Perforation resistance with the conical nail 3,0 mm<br/>    diameter.....</b> | <b>13</b>   |
| <b>Bibliography.....</b>  | <b>18</b>   |