

DIN EN 17353:2025-12 (E)

Protective clothing - Enhanced visibility equipment for medium risk situations - Test methods and requirements (includes Amendment :2025)

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 6 |
| 4 | Types and minimum area requirements | 9 |
| 4.1 | Types | 9 |
| 4.2 | Minimum area requirements | 10 |
| 5 | Design requirements | 11 |
| 5.1 | Size designation | 11 |
| 5.2 | Type A | 11 |
| 5.2.1 | General | 11 |
| 5.2.2 | Visibility from all sides | 11 |
| 5.3 | Type B | 12 |
| 5.3.1 | General | 12 |
| 5.3.2 | Type B1 - Free hanging devices | 12 |
| 5.3.3 | Type B2 - Equipment for limbs | 12 |
| 5.3.4 | Type B3 - Equipment for the torso or the torso and limbs | 12 |
| 5.4 | Type AB | 13 |
| 6 | Material requirements | 13 |
| 6.1 | Requirements for non-fluorescent material, fluorescent material and combined performance material | 13 |
| 6.1.1 | Colour performance requirements of new material | 13 |
| 6.1.2 | Colour after Xenon test | 15 |
| 6.1.3 | Colour fastness of fluorescent material and all non-fluorescent material layers after test exposure | 15 |
| 6.2 | Dimensional change of fluorescent material and non-fluorescent material | 16 |
| 6.3 | Photometric and physical performance requirements for the separate performance and combined performance materials | 16 |
| 6.3.1 | Retroreflective performance requirements of new material | 16 |
| 6.3.2 | Type B1 - Free hanging devices | 17 |
| 6.3.3 | Type B2, B3 and AB - removable or permanently applied materials or devices | 17 |
| 6.4 | Retroreflective performance requirements after test exposure | 18 |
| 6.4.1 | General | 18 |
| 6.4.2 | Separate performance material | 19 |
| 6.4.3 | Combined performance material | 19 |
| 6.4.4 | Orientation sensitive materials | 19 |
| 7 | Test methods | 19 |
| 7.1 | Sampling and conditioning | 19 |
| 7.2 | Determination of colour | 19 |
| 7.3 | Method of determination of retroreflective photometric performance | 20 |
| 7.3.1 | General | 20 |
| 7.3.2 | Type B1 devices | 20 |
| 7.3.3 | Type B2 and B3 and Type AB devices or garments | 20 |
| 7.4 | Test exposure of retroreflective material | 20 |

| | | |
|--|--|----|
| 7.4.1 | Abrasion | 20 |
| 7.4.2 | Folding at cold temperatures | 21 |
| 7.4.3 | Exposure to temperature variation | 21 |
| 7.4.4 | Rainfall | 21 |
| 7.4.5 | Free fall test | 21 |
| 7.4.6 | Influence of water (water immersion) | 21 |
| 7.5 | Ageing | 21 |
| 7.5.1 | General | 21 |
| 7.5.2 | Washing | 22 |
| 7.5.3 | Dry cleaning | 22 |
| 8 | Marking | 22 |
| 9 | Information supplied by the manufacturer | 23 |
| Annex A (informative) Examples of garments or devices according to types and classes | | 24 |
| Annex B (informative) Examples of different types of equipment | | 26 |
| Annex C (informative) Examples on how to determine visibility from all sides for Type A garments | | 27 |
| Annex D (informative) Possible designs for the placement of fluorescent material on garments | | 28 |
| Annex E (informative) Examples of Type B2 and Type B3 garment | | 29 |
| Annex ZA (informative) Relationship between this European Standard and the essential requirements of Regulation 2016/425 aimed to be covered | | 31 |
| Bibliography | | 32 |