

# ISO 28598-2:2017-10 (E)

## Acceptance sampling procedures based on the allocation of priorities principle (APP) - Part 2: Coordinated single sampling plans for acceptance sampling by attributes

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vii
1	Scope .....	1
2	Normative references .....	1
3	Terms, definitions, symbols and abbreviations .....	2
3.1	Terms and definitions .....	2
3.2	Symbols and abbreviations .....	3
4	Selection from among sampling systems by attributes .....	4
4.1	Relationship between sampling systems .....	4
5	Lot quality .....	5
5.1	Lot quality measures .....	5
5.2	Satisfactory and unsatisfactory lots .....	5
5.3	Types of requirements .....	5
5.4	Preferred NQLs .....	5
5.5	Disposition of unsatisfactory lots .....	5
6	Limits for other party's risk .....	6
6.1	Supplier's sampling plans .....	6
6.1.1	Assignment of a customer's risk on supplier inspection .....	6
6.1.2	Trust levels .....	6
6.1.3	Supplementary trust levels .....	6
6.2	Customer's sampling plans .....	6
6.3	Permissible sampling plans .....	8
6.4	Coordination of supplier's and customer's sampling plans .....	8
6.5	Rule of the third party inspection .....	8
7	Inspecting party's risk .....	9
7.1	Supplier's sampling plans .....	9
7.2	Customer's sampling plans .....	9
8	Basic data .....	9
8.1	Supplier's sampling plans .....	9
8.2	Customer's sampling plans .....	9
9	Catalogue of permissible sampling plans .....	9
9.1	Composition of tables .....	9
9.2	Tables for supplier permissible single sampling plans .....	10
9.2.1	Description of supplier single sampling tables .....	10
9.2.2	Tables for percent nonconforming .....	10
9.2.3	Tables for nonconformities per 100 items .....	11
9.2.4	Table entries .....	11
9.3	Tables for customer permissible single sampling plans .....	11

<b>10</b>	<b>Choosing supplier's single sampling plans .....</b>	<b>11</b>
<b>10.1</b>	<b>Rules for choosing permissible single sampling plans .....</b>	<b>11</b>
<b>10.2</b>	<b>Recommendations on selecting a preferred plan from those permissible for T2 and T3 trust levels .....</b>	<b>12</b>
<b>10.2.1</b>	<b>Known estimate of a lot quality level .....</b>	<b>12</b>
<b>10.2.2</b>	<b>Known standard or estimate of a process quality level .....</b>	<b>12</b>
<b>11</b>	<b>Choosing customer's single sampling plans .....</b>	<b>12</b>
<b>11.1</b>	<b>General recommendations .....</b>	<b>12</b>
<b>11.2</b>	<b>Use of customer's sampling tables for known sample size .....</b>	<b>12</b>
<b>12</b>	<b>Sampling inspection for NQL = 0 .....</b>	<b>13</b>
<b>Annex A (normative)</b>	<b>Tables for acceptance single sampling plans by attributes .....</b>	<b>14</b>
<b>Annex B (informative)</b>	<b>Examples of application of catalogued permissible sampling plans .....</b>	<b>42</b>
<b>Annex C (informative)</b>	<b>Theoretical justification .....</b>	<b>46</b>
<b>Bibliography</b>	<b>.....</b>	<b>51</b>