

# ISO 11843-6:2019 (E)

## Capability of detection — Part 6: Methodology for the determination of the critical value and the minimum detectable value in Poisson distributed measurements by normal approximations

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Measurement system and data handling
5	Computation by approximation
5.1	The critical value based on the normal distribution
5.2	Determination of the critical value of the response variable
5.3	Sufficient capability of the detection criterion
5.4	Confirmation of the sufficient capability of detection criterion
6	Reporting the results from an assessment of the capability of detection
7	Reporting the results from an application of the method
Annex A	(informative) Symbols used in this document
Annex B	(informative) Estimating the mean value and variance when the Poisson distribution is approximated by the normal distribution
Annex C	(informative) An accuracy of approximations
Annex D	(informative) Selecting the number of channels for the detector
Annex E	(informative) Examples of calculations
E.1	Example 1: Measurement of hazardous substances by X-ray diffractometry (XRD)
E.1.1	Statistical analysis
E.1.2	Estimating the minimum detectable concentration of asbestos
E.2	Example 2: Measurement of contamination on the surface of silicon wafers by X-ray photoelectron spectroscopy (XPS)
E.2.1	Statistical analysis
E.2.2	Estimating the minimum detectable concentration of hydrocarbon by the approximation

Page count: 23