ISO/TR 11843-8:2021-11 (E)

Capability of detection - Part 8: Guidance for the implementation of the ISO 11843 series

Contents

Page

Foreword iv

0 Introduction v

1 Scope 1

2 Normative references 1

3 Terms,definitionsandsymbols 1
3.1 Terms and definitions 1
3.2 Symbols 1

4 Historical survey of terms 3

5 Fundamental concepts of detection limit (minimum detectable value in ISO 11843) 4
5.1 General 4
5.2 General definition of detection limit 4
5.3 Detection limit with probability 5
5.4 Detection limit with probabilities and 6

6 Pragmatic view of and 9
6.1 Statistical definitions of and 9
6.2 Actual examples of and values 9

7 In-depth explanations and examples of the Parts in the ISO 11843 series 9
7.1 General 9
7.2 ISO 11843-3 and ISO 11843-4 10
7.2.1 General 10
7.2.2 Number of repeated measurements, J and K 10
7.2.3 Determination of the minimum detectable value 11
7.2.4 Confirmation of the minimum detectable value for an obtained experimental value with the number of repeated measurements, N 11
7.2.5 Number of repeated measurements, J and K, in ISO 11843-5 and ISO 11843-7 13
7.3 ISO 11843-6 13
7.3.1 Overview of ISO 11843-6 13
7.3.2 Features of pulse count measurement 13
7.4 Example from ISO 11843-7 19

Annex A (informative) Standard normal random variable 23

Annex B (informative) Difference between the power of test and the minimum detectable value 25

Annex C (informative) Calculation example from ISO 11843-4 27

Annex D (informative) Calculation example from ISO 11843-6:2019, Annex E (Measurement of hazardous substances by X-ray diffractometer) 28

Annex E (informative) Comparison between the Poisson exact arithmetic and the approximations 31

Annex F (informative) Association of IUPAC recommended detection limit with the ISO 11843 series 36

Bibliography 38