

# ISO 2859-3:2005-05 (E)

## Sampling procedures for inspection by attributes - Part 3: Skip-lot sampling procedures

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions and symbols .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.2</b>	<b>Symbols and abbreviated terms .....</b>	<b>3</b>
<b>4</b>	<b>General requirements .....</b>	<b>3</b>
<b>5</b>	<b>Supplier and product qualification .....</b>	<b>4</b>
<b>5.1</b>	<b>Supplier qualification .....</b>	<b>4</b>
<b>5.2</b>	<b>Product qualification .....</b>	<b>5</b>
<b>5.3</b>	<b>Qualification score .....</b>	<b>6</b>
<b>5.4</b>	<b>Example for product qualification .....</b>	<b>8</b>
<b>6</b>	<b>Skip-lot sampling procedures .....</b>	<b>9</b>
<b>6.1</b>	<b>General .....</b>	<b>9</b>
<b>6.2</b>	<b>Initial inspection frequency and its determination .....</b>	<b>11</b>
<b>6.3</b>	<b>Inspection frequency and shifting .....</b>	<b>11</b>
<b>6.4</b>	<b>Sampling plans, lot selection and inspection procedures (States 2 and 3) .....</b>	<b>14</b>
<b>6.5</b>	<b>Skip-lot interruption .....</b>	<b>15</b>
<b>6.6</b>	<b>Requalification .....</b>	<b>16</b>
<b>6.7</b>	<b>Product disqualification .....</b>	<b>16</b>
<b>6.8</b>	<b>Supplier disqualification and suspension .....</b>	<b>17</b>
<b>7</b>	<b>Supplier responsibilities .....</b>	<b>17</b>
<b>8</b>	<b>Inspection agency and responsible authority responsibilities .....</b>	<b>18</b>
<b>8.1</b>	<b>General .....</b>	<b>18</b>
<b>8.2</b>	<b>Responsibilities on supplier qualification .....</b>	<b>19</b>
<b>8.3</b>	<b>Other responsibilities .....</b>	<b>19</b>
<b>9.1</b>	<b>Limitations .....</b>	<b>20</b>
<b>9.2</b>	<b>Relation to reduced inspection .....</b>	<b>20</b>
<b>10</b>	<b>Additional information .....</b>	<b>21</b>
<b>10.1</b>	<b>Design basis .....</b>	<b>21</b>
<b>10.2</b>	<b>Statistical characteristics of the skip-lot procedures .....</b>	<b>21</b>
<b>Annex A (normative) Optional requirements to be agreed prior to product qualification .....</b>		<b>23</b>
<b>Annex B (normative) Procedures for random selection at specified inspection frequency .....</b>		<b>25</b>
<b>Annex C (informative) Factors used in deciding between skip-lot inspection and reduced inspection .....</b>		<b>27</b>
<b>Bibliography .....</b>		<b>29</b>