

ISO 3951-3:2007-05 (E)

Sampling procedures for inspection by variables - Part 3: Double sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
4	Symbols and abbreviations	7
5	Acceptance quality limit (AQL)	9
6	Switching rules for normal, tightened and reduced inspection	10
7	Relation to ISO 2859-1	10
8	Limiting quality protection	11
9	Planning	12
10	Choice between variables and attributes	12
11	Choice of method	13
12	Choice between single and double sampling plans	13
13	Choice of inspection level and AQL	14
14	Choice of sampling scheme	14
15	Preliminary operations	15
16	Standard univariate "s" method procedures	16
17	Standard univariate "" method procedures	25
18	Procedure during continuing inspection	32
19	Normality and outliers	32
20	Records	32
21	Operation of switching rules	33
22	Discontinuation and resumption of inspection	33
23	Switching between the "s" and "" methods	34

Annex A (informative) Standard multivariate "s" method procedures for double sampling with independent quality characteristics	72
Annex B (informative) Standard multivariate "" method procedures for double sampling with independent quality characteristics	74
Annex C (informative) Standard multivariate combined "s" and "" method procedures for double sampling with independent quality characteristics	76
Annex D (informative) Location of text on key features	78
Annex E (normative) Estimating the process fraction nonconforming	81
Annex F (informative) Form k "s" method single sampling plans matched to the corresponding single sampling plans by attributes	87
Annex G (informative) Form k "" method single sampling plans matched to the corresponding single sampling plans by attributes	91
Annex H (informative) Average sample sizes for double sampling by variables: "s" method	95
Annex I (informative) Producer's risks for the "s" method	98
Annex J (informative) Tabulated operating characteristics for double sampling plans with known process standard deviation	100
Annex K (informative) Ratios of ASSIs of double sampling plans under normal inspection to the sample size of the corresponding single sampling plan by variables	107
Annex L (informative) Ratios of the ASSIs of double sampling plans by variables to the ASSIs of corresponding plans by attributes	109
Annex M (informative) Design methodology	112
Bibliography	113