

# ISO 3951-3:2007-05 (E)

## Sampling procedures for inspection by variables - Part 3: Double sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1 Scope .....		1
2 Normative references .....		2
3 Terms and definitions .....		2
4 Symbols and abbreviations .....		7
5 Acceptance quality limit (AQL) .....		9
6 Switching rules for normal, tightened and reduced inspection .....		10
7 Relation to ISO 2859-1 .....		10
8 Limiting quality protection .....		11
9 Planning .....		12
10 Choice between variables and attributes .....		12
11 Choice of method .....		13
12 Choice between single and double sampling plans .....		13
13 Choice of inspection level and AQL .....		14
14 Choice of sampling scheme .....		14
15 Preliminary operations .....		15
16 Standard univariate "s" method procedures .....		16
17 Standard univariate "" method procedures .....		25
18 Procedure during continuing inspection .....		32
19 Normality and outliers .....		32
20 Records .....		32
21 Operation of switching rules .....		33
22 Discontinuation and resumption of inspection .....		33
23 Switching between the "s" and "" methods .....		34

<b>Annex A (informative) Standard multivariate "s" method procedures for double sampling with independent quality characteristics .....</b>	<b>72</b>
<b>Annex B (informative) Standard multivariate "" method procedures for double sampling with independent quality characteristics .....</b>	<b>74</b>
<b>Annex C (informative) Standard multivariate combined "s" and "" method procedures for double sampling with independent quality characteristics .....</b>	<b>76</b>
<b>Annex D (informative) Location of text on key features .....</b>	<b>78</b>
<b>Annex E (normative) Estimating the process fraction nonconforming .....</b>	<b>81</b>
<b>Annex F (informative) Form k "s" method single sampling plans matched to the corresponding single sampling plans by attributes .....</b>	<b>87</b>
<b>Annex G (informative) Form k "" method single sampling plans matched to the corresponding single sampling plans by attributes .....</b>	<b>91</b>
<b>Annex H (informative) Average sample sizes for double sampling by variables: "s" method .....</b>	<b>95</b>
<b>Annex I (informative) Producer's risks for the "s" method .....</b>	<b>98</b>
<b>Annex J (informative) Tabulated operating characteristics for double sampling plans with known process standard deviation .....</b>	<b>100</b>
<b>Annex K (informative) Ratios of ASSIs of double sampling plans under normal inspection to the sample size of the corresponding single sampling plan by variables .....</b>	<b>107</b>
<b>Annex L (informative) Ratios of the ASSIs of double sampling plans by variables to the ASSIs of corresponding plans by attributes .....</b>	<b>109</b>
<b>Annex M (informative) Design methodology .....</b>	<b>112</b>
<b>Bibliography .....</b>	<b>113</b>