

ISO/TR 21704:2017-02 (E)

Toughness of round steel link chains - Test with sub-size specimens

| Contents | | Page |
|-------------------------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Abbreviated terms | 1 |
| 5 | Target objective | 2 |
| 6 | Chain manufacturers | 2 |
| 7 | Tested chain steels | 2 |
| 8 | Equipment, specimen geometry and sampling | 3 |
| 9 | Results | 4 |
| 9.1 | Notch impact energy temperature of the tested steels | 4 |
| 9.2 | Comparison of the test results and test equipment of manufacturer 1 and manufacturer 2 | 4 |
| 9.3 | Conversion of the characteristic values determined at sub-size notch impact specimens .. | 4 |
| 9.4 | Validation of the conversion | 5 |
| 9.5 | Scatter of the notch impact energy values determined with sub-size specimens | 5 |
| 9.6 | Brittle fracture transition temperature | 6 |
| 10 | Specimen extension | 7 |
| 10.1 | Laser welding | 7 |
| 10.2 | Friction welding | 7 |
| 10.3 | Extended super sub-size notch impact specimens | 7 |
| 11 | Derivation of the toughness criteria for characteristic values determined with sub-size notch impact specimens | 8 |
| 12 | Characteristic values of the round steel link chains from manufacturer M3 and M4 | 9 |
| 12.1 | Manufacturer M3 | 9 |
| 12.2 | Manufacturer M4 | 9 |
| 13 | Characteristic values of the sub-size notch impact specimens, temperature and notch impact energy | 9 |
| 14 | Requirements to the characteristic toughness values of the sub-size and the super sub-size notch impact specimens | 10 |
| 15 | Status of international standardization | 11 |
| Annex A (informative) Figures | | 12 |
| Bibliography | | 43 |