ISO 4778:2019 (E)

Round steel short link chains for lifting purposes — Chain slings of welded construction — Grade 8

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Requirements

- 4.1 Chain sling
- 4.2 Components
- 4.2.1 Chain legs
- 4.2.2 Master links
- 4.2.3 Intermediate master links, joining links and end links
- 4.2.4 Hooks
- 4.2.5 Other forged components
- 4.3 Working load limit (WLL)
- 4.4 Mechanical requirements
- 4.4.1 General
- 4.4.2 Single leg chain sling
- 4.4.3 Double leg chain sling
- 4.4.4 Three and four leg chain sling

5 Marking

- 5.1 General
- 5.2 Single leg chain sling
- 5.3 Double leg chain sling
- 5.4 Three and four leg chain sling

6 Manufacturer's certificate

7 Examples of chain slings

Annex A (informative) Bases for calculation

- A.1 Working load limit (WLL)
- A.1.1 General
- A.1.2 Single leg chain sling with inclination angle β = 0°
- A.1.3 Double leg chain sling with inclination angle 0° < β ≤ 45°
- A.1.4 Double leg chain sling with inclination angle 45° < β ≤ 60°
- A.1.5 Intermediate master link with inclination angle 0° < β ≤ 37,5° 1 1 Developed at the National Physical Laboratory, United Kingdom.
- A.1.6 Three and four leg chain sling with inclination angle 0° < β ≤ 45°
- A.1.7 Three and four leg chain sling with inclination angle 45° < β ≤ 60°
- A.2 Manufacturing proof force (MPF)
- A.2.1 General
- A.2.2 Test section 1 (TS1)
- A.2.3 Test section 2 (TS2)
- A.2.4 Test section 3 (TS3)
- A.2.5 Test section 4 (TS4)
- A.3 Breaking force (BF)
- A.3.1 General
- A.3.2 Test section 1 (TS1)
- A.3.3 Test section 2 (TS2)

A.3.4 Test section 3 (TS3)
A.3.5 Test section 4 (TS4)

Annex B (informative) Correlations, grade 8

Annex C (informative) Compatibility of chain slings to shank hooks

Annex D (informative) Information for the calculation of the nominal diameter of links

Page count: 26