

ISO/TR 23602 :2005-07 (E)

Toughness of chain steels

Contents	Page
Foreword.....	v
1 Scope	1
2 Normative references	1
3 Types of chain and extraction of specimens	2
4 Materials, chemical composition and heat-treatment.....	2
5 Tensile tests on chains	2
6 Conventional tensile tests on standard specimens.....	3
7 Notch impact tests.....	3
8 Fracture mechanics tests on notched chain links with slits.....	4
9 Fracture mechanics tests on notched three-point bend specimens with slits and fatigue cracks.....	6
10 Correlation between the load-bearing capacity of chain links containing slits and material toughness.....	7
11 Fracture mechanics derivation of chain links	7
12 Load-bearing and brittle fracture transition concept — Requirements	8
13 Correlation of test results with data from the literature	9
14 Summary.....	9
Figure 1 — Results C_V tests: Standard specimen (EN 10045).....	11
Figure 2 — Load-time diagram for instrumented C_V	13
Figure 3 — Crack arrest load as function of temperature	14
Figure 4 — Noncrystalline area in C_V — Test.....	15
Figure 5 — Load–COD diagram for TPB specimens with fatigue crack and eroded slits material type T, $T = -40\text{ °C}$	16
Figure 6 — Load–COD diagram for TPB specimens with fatigue crack and eroded slits material grade VH, $T = -40\text{ °C}$	17
Figure 7 — Comparison of pre-cracked and eroded chain link material grade VH, $T = -40\text{ °C}$	18
Figure 8 —Chain link specimen	19
Figure 9 — Clip gauge fixed in chain link.....	20
Figure 10 — Calibration of clip gauge for COD measurement.....	21
Figure 11 — Test specimen at -40 °C , three links.....	21
Figure 12 — Effect of slit size on loadability of chain, $T = -40\text{ °C}$	22
Figure 13 — Load–COD diagram for tension tests on chains with eroded slit, $T = -40\text{ °C}$, $ald = 0,22$	23
Figure 14 — Load–COD diagram for tension tests on chains with eroded slit, $T = -40\text{ °C}$, $ald = 0,43$	24
Figure 15 — Load–COD diagram for tension tests on chains with eroded slit, $T = -40\text{ °C}$, $ald = 0,64$	25
Figure 16 — Stable crack growth chain Type T, $ald = 0,22$ — Marked by heat tinting	26
Figure 17 — Effect of slit size on absorbed energy of chains, $T = -40\text{ °C}$	27

Figure 18 — Fracture mechanics tests on TPB specimens.....	28
Figure 19 — Fracture mechanics concepts.....	29
Figure 20 — Fracture toughness values for TPB specimens with eroded slits, $T = -40\text{ }^{\circ}\text{C}$, $alw = 0,5$	30
Figure 21 — R-curves material Type T, $T = -40\text{ }^{\circ}\text{C}$, $alw = 0,4$	31
Figure 22 — R-curves material Type T, $T = -40\text{ }^{\circ}\text{C}$, $alw = 0,4$	32
Figure 23 — Nominal fracture stress in chain link, correlated with fracture mechanics properties.....	33
Figure 24 — Nominal fracture stress in chain link correlated with fracture mechanics properties.....	34
Figure 25 — Correlation of fracture load and C_V toughness	35
Figure 26 — Correlation nominal fracture stress of chain and C_V toughness.....	36
Figure 27 — Finite element analysis of chain links with eroded slit, $ald = 0$	37
Figure 28 — Finite element analysis of chain links with eroded slit, $ald = 0,22$	37
Figure 29 — Finite element analysis of chain links with eroded slit, $ald = 0,64$	38
Figure 30 — Nominal stresses in cracked chain link	39
Figure 31 — Correction factor for long bending bars ^[5]	40
Figure 32 — Stress intensity factor for long bending bars	41
Figure 33 — Safety relations between requirement and service conditions	42
Figure 34 — Nominal fracture stress in chain link, correlated with fracture mechanics properties.....	43
Figure 35 — Correlation nominal fracture stress of chain and C_V toughness.....	44
Figure 36 — Correlation of fracture and C_V toughness pre-cracked TPB specimens	45
Table 1 — Chemical composition of the chain steels	46
Table 2 — Tensile test results on chain specimens (5 links)	46
Table 3 — Tensile test results on standard specimens (EN 10002, B6*30) $T = -40\text{ }^{\circ}\text{C}$	46
Table 4 — Results of C_V tests.....	47
Table 5 — Crack arrest loads of C_V tests	47
Table 6 — Noncrystalline area of C_V specimens	47
Table 7 — Transition behaviour of chain materials.....	47
Table 8 — Maximum loads of chain-tests at $-40\text{ }^{\circ}\text{C}$	48
Table 9 — Maximum displacement for chain tests, $T = -40\text{ }^{\circ}\text{C}$	48
Table 10 — Absorbed energy of the chain tests, $T = -40\text{ }^{\circ}\text{C}$	48
Table 11 — Evaluation of fracture mechanics test on TPB specimens	49
Table 12 — Fracture mechanics tests on TPB specimens with eroded slits.....	49
Table 13 — Fracture mechanics tests on TPB specimens with fatigue cracks, $T = -40\text{ }^{\circ}\text{C}$	49
Table 14 — R curves data material Type T	50
Table 15 — Calculation of K_Q values for chain grade VH	50
Bibliography	51