ISO 6218:2015-09 (E)

Inland navigation vessels - Manually- and power-operated coupling devices for pushing un its and coupled vessels - Safety requirements and main dimensions

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Safety requirements 2
4.1 General 2
4.1.1 Components 2
4.1.2 Requirements 4
4.2 Limitation of actuating power for power operated coupling devices 5
4.3 Limitation of rope speed 5
4.4 Strength requirements 5

5 Models 5
5.1 Operation 5
5.2 Position of handwheel/motor 5
5.3 With or without tensioning device 6

6 Design 6
6.1 Rope drum 6
6.1.1 Drum capacity 6
6.1.2 Drum diameter 6
6.1.3 Rope fastening 6
6.2 Handwheel 6
6.2.1 Clearances 6
6.2.2 Construction 6
6.2.3 Handhold 6
6.3 Power-driven equipment 7
6.4 Combined operating modes 7
6.5 Arresting device 7
6.5.1 General 7
6.5.2 Arresting devices for manually operated coupling devices 7
6.5.3 Arresting devices for power-driven coupling devices 7
6.6 Protective device 7
6.7 Footbrakes for manually operated coupling devices 7
6.8 Brakes for power operated coupling devices 7
6.9 Gears 8
6.10 Tensioning device for manually operated coupling systems 8
6.11 Change gear for manually operated coupling devices 8
6.12 Foundation 8
6.13 Guide track 8

7 Dimensions and characteristic values 8
7.1 General 8
7.2 Characteristic values 8
7.3 Main dimensions of the coupling device 9
7.3.1 Manually operated coupling devices 9
7.3.2 Power operated coupling devices 11

7.4 Arrangement of foundation 12

8 Material 12

9 Operating instructions and assembly instructions 13
9.1 General 13
9.2 Assembly instructions 13
9.3 Operating instructions 13

10 Designation 13

11 Marking 14

Annex A (normative) Individual and type testing 15

Bibliography 16