

ISO 12217-1:2015-10 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 1: Non-sailing boats of hull length greater than or equal to 6 m

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
3.1	Primary	2
3.2	Downflooding	4
3.3	Dimensions, areas and angles	5
3.4	Condition, mass and volume	7
3.5	Other terms and definitions	9
4	Symbols	12
5	Procedure	13
5.1	Maximum load	13
5.2	Sailing or non-sailing	13
5.3	Tests and calculations to be applied	14
5.4	Variation in input parameters	15
6	Tests, calculations and requirements	15
6.1	Downflooding	15
6.1.1	Downflooding openings	15
6.1.2	Downflooding height	17
6.1.3	Downflooding angle	20
6.2	Offset-load test	20
6.2.1	Objective	20
6.2.2	Test	21
6.2.3	Requirements	21
6.3	Resistance to waves and wind	21
6.3.1	General	21
6.3.2	Rolling in beam waves and wind	21
6.3.3	Resistance to waves	22
6.4	Heel due to wind action	23
6.4.1	General	23
6.4.2	Calculation	23
6.4.3	Requirement	24
6.5	Recess size	24
6.5.1	Application	24
6.5.2	Simplified methods	25
6.5.3	Direct calculation method	26
6.5.4	Design category C boats using option 6	27
6.6	Habitable multihull boats	27
6.7	Motor sailers	27
6.7.1	General	27
6.7.2	Requirement	28
6.8	Flotation requirements	28
6.9	Detection and removal of water	28

7	Application	29
7.1	Deciding the design category	29
7.2	Meaning of the design categories	29
Annex A (normative)	Full method for required downflooding height	31
Annex B (normative)	Method for offset-load test	33
Annex C (normative)	Methods for calculating downflooding angle	41
Annex D (normative)	Method for measuring freeboard margin	43
Annex E (normative)	Determining the curve of righting moments	45
Annex F (normative)	Method for level flotation test	48
Annex G (normative)	Flotation material and elements	53
Annex H (normative)	Information for owner's manual	55
Annex I (informative)	Summary of requirements	57
Annex J (informative)	Worksheets	58
Annex K (informative)	Illustration of recess retention level	75
Bibliography	76