

ISO 12217-2:2015-10 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 2: Sailing boats of hull length greater than or equal to 6 m

Contents		Page
Foreword		v
Introduction		vii
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
3.1	Primary	2
3.2	Hazards	4
3.3	Downflooding	4
3.4	Dimensions, areas and angles	5
3.5	Condition, mass and volume	6
3.6	Other terms and definitions	9
4	Symbols	12
5	Procedure	13
5.1	Maximum load	13
5.2	Sailing or non-sailing	13
5.3	Tests, calculations and requirements to be applied	14
5.4	Variation in input parameters	14
6	Requirements for monohull boats	14
6.1	Requirements to be applied	14
6.2	Downflooding	15
6.2.1	Downflooding openings	15
6.2.2	Downflooding height	18
6.2.3	Downflooding angle	19
6.3	Recess size	19
6.3.1	Application	19
6.3.2	Simplified methods	20
6.3.3	Direct calculation method	22
6.4	Minimum righting energy	22
6.5	Angle of vanishing stability	22
6.5.1	Normal requirement	23
6.5.2	Alternative requirement for design category B	23
6.6	Stability index (STIX)	24
6.6.1	Method	24
6.6.2	Dynamic stability factor (FDS)	25
6.6.3	Inversion recovery factor (FIR)	25
6.6.4	Knockdown recovery factor (FKR)	25
6.6.5	Displacement-length factor (FDL)	26
6.6.6	Beam-displacement factor (FBD)	26
6.6.7	Wind moment factor (FWM)	26
6.6.8	Downflooding factor (FDF)	27
6.6.9	Calculation of the stability index (STIX)	27
6.7	Knockdown-recovery test	28
6.8	Wind stiffness test	29
6.8.1	General	29

6.8.2	Practical test	29
6.8.3	Compliance by calculation	30
6.8.4	Requirements	30
6.9	Flotation requirements	31
6.10	Capsize-recovery test	32
6.11	Detection and removal of water	33
7	Requirements for catamarans, trimarans and form-stable monohulls	34
7.1	Requirements to be applied	34
7.2	Downflooding openings	34
7.3	Downflooding height	34
7.4	Recess size	34
7.5	Stability information	35
7.6	Safety signs	36
7.7	Bare poles factor	37
7.8	Rolling in breaking waves	37
7.9	Pitchpoling	37
7.10	Diagonal stability	38
7.11	Habitable multihull boats	38
7.12	Buoyancy when inverted	39
7.13	Escape after inversion	40
8	Safety signs	41
9	Application	42
9.1	Deciding the design category	42
9.2	Meaning of the design categories	42
Annex A (normative) Full method for required downflooding height		44
Annex B (normative) Methods for calculating downflooding angle		47
Annex C (normative) Determining the curve of righting moments		50
Annex D (normative) Method for calculating reserve of buoyancy after inversion or swamping		53
Annex E (normative) Flotation material and elements		55
Annex F (normative) Information for owner's manual		57
Annex G (normative) Determination of safe wind speed information		61
Annex H (normative) Determination of longitudinal righting characteristics		64
Annex I (informative) Summary of requirements		67
Annex J (informative) Worksheets		70
Annex K (informative) Illustration of recess retention level		89
Bibliography		90