ISO 12217-2:2015-10 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 2: Sailing boats of hull length greater than or equal to 6 m

Contents

Page

Foreword v

Introduction vii

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 2
3.1 Primary 2
3.2 Hazards 4
3.3 Downflooding 4
3.4 Dimensions, areas and angles 5
3.5 Condition, mass and volume 6
3.6 Other terms and definitions 9

4 Symbols 12

5 Procedure 13
5.1 Maximum load 13
5.2 Sailing or non-sailing 13
5.3 Tests, calculations and requirements to be applied 14
5.4 Variation in input parameters 14

6 Requirements for monohull boats 14
6.1 Requirements to be applied 14
6.2 Downflooding 15
6.2.1 Downflooding openings 15
6.2.2 Downflooding height 18
6.2.3 Downflooding angle 19
6.3 Recess size 19
6.3.1 Application 19
6.3.2 Simplified methods 20
6.3.3 Direct calculation method 22
6.4 Minimum righting energy 22
6.5 Angle of vanishing stability 22
6.5.1 Normal requirement 23
6.5.2 Alternative requirement for design category B 23
6.6 Stability index (STIX) 24
6.6.1 Method 24
6.6.2 Dynamic stability factor (FDS) 25
6.6.3 Inversion recovery factor (FIR) 25
6.6.4 Knockdown recovery factor (FKR) 25
6.6.5 Displacement-length factor (FDL) 26
6.6.6 Beam-displacement factor (FBD) 26
6.6.7 Wind moment factor (FWM) 26
6.6.8 Downflooding factor (FDF) 27
6.6.9 Calculation of the stability index (STIX) 27
6.7 Knockdown-recovery test 28
6.8 Wind stiffness test 29
6.8.1 General 29

6.8.2 Practical test 29
6.8.3 Compliance by calculation 30
6.8.4 Requirements 30
6.9 Flotation requirements 31
6.10 Capsize-recovery test 32
6.11 Detection and removal of water 33

7 Requirements for catamarans, trimarans and form-stable monohulls 34
7.1 Requirements to be applied 34

7.2 Downflooding openings 34
7.3 Downflooding height 34
7.4 Recess size 34
7.5 Stability information 35
7.6 Safety signs 36
7.7 Bare poles factor 37
7.8 Rolling in breaking waves 37
7.9 Pitchpoling 37
7.10 Diagonal stability 38
7.11 Habitable multihull boats 38
7.12 Buoyancy when inverted 39
7.13 Escape after inversion 40

8 Safety signs 41

9 Application 42
9.1 Deciding the design category 42
9.2 Meaning of the design categories 42

Annex A (normative)Fullmethodforrequireddownfloodingheight 44

Annex B (normative)Methodsforcalculatingdownfloodingangle 47

Annex C (normative) Determining the curve of righting moments 50

Annex D (normative) Method for calculating reserve of buoyancy after inversion or swamping 53

Annex E (normative) Flotation material and elements 55

Annex F (normative) Information for owner's manual 57

Annex G (normative) Determination of safe wind speed information 61

Annex H (normative) Determination of longitudinal righting characteristics 64

Annex I (informative) Summary of requirements 67

Annex J (informative) Worksheets 70

Annex K (informative) Illustration of recess retention level 89

Bibliography 90