

ISO 19030-2:2016-11 (E)

Ships and marine technology - Measurement of changes in hull and propeller performance - Part 2: Default method

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Measurement parameters	2
4.1	General	2
4.2	Primary parameters	2
4.3	Secondary parameters	3
4.4	Sensor installation, maintenance and calibration	3
4.5	External information	4
5	Measurement procedures	5
5.1	General	5
5.2	Data acquisition	5
5.3	Data storage	6
5.4	Data preparation	6
5.4.1	General	6
5.4.2	Data preparation frequency	7
5.4.3	Data retrieval	7
5.4.4	Data compilation	7
5.4.5	Data filtering and validation	8
5.4.6	Correction for environmental factors	8
5.4.7	Calculation of performance values (PVs)	8
6	Calculation of performance indicators (PIs)	9
6.1	General	9
6.2	Definition of PIs	9
6.3	Calculation of PIs	9
6.3.1	General	9
6.3.2	Determination of reference conditions	10
6.3.3	Establishment of reference period and evaluation period	10
6.3.4	Extraction of subsets of PVs from the complete set with PVs that fulfil reference conditions for reference conditions for reference period(s) and evaluation period	11
6.3.5	Calculation of the PI	11
7	Accuracy of PIs	12
7.1	General	12
7.2	Guidance on the expected accuracy of PIs	12
Annex A (informative) Process of this document		14
Annex B (normative) Approximating delivered power based on calculations of shaft power		15
Annex C (normative) Approximating delivered power based on calculations of brake power		16

Annex D (informative) SFOC reference curve	19
Annex E (normative) Calculation of true wind speed and direction	21
Annex F (informative) Procedure to obtain ship specific power-speed-draught-trim databases	24
Annex G (normative) Correction for wind resistance	25
Annex H (informative) Protocol to export data from data logger	27
Annex I (normative) Outlier detection	32
Annex J (normative) Validation	34
Annex K (informative) Method for calculating power performance values (PPV) and power performance indicators (PPI)	35
Bibliography	37