

# ISO 8099-1:2018-02 (E)

## Small craft - Waste systems - Part 1: Waste water retention

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative reference .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>General requirements .....</b>	<b>2</b>
<b>5</b>	<b>Materials .....</b>	<b>3</b>
<b>6</b>	<b>Plumbing system .....</b>	<b>3</b>
<b>6.1</b>	<b>Hoses and piping .....</b>	<b>3</b>
<b>6.2</b>	<b>Seacock fitting .....</b>	<b>3</b>
<b>7</b>	<b>Vent system .....</b>	<b>3</b>
<b>7.1</b>	<b>Venting of gases .....</b>	<b>3</b>
<b>7.1.1</b>	<b>Heel angles .....</b>	<b>3</b>
<b>7.1.2</b>	<b>Inside diameter of fittings .....</b>	<b>3</b>
<b>7.1.3</b>	<b>Prevention of clogging -- Pressure resistance .....</b>	<b>4</b>
<b>7.1.4</b>	<b>Flow area .....</b>	<b>4</b>
<b>7.2</b>	<b>Venting of tanks .....</b>	<b>4</b>
<b>7.2.1</b>	<b>Rigid tanks with capacity of less than 400 l .....</b>	<b>4</b>
<b>7.2.2</b>	<b>Rigid tanks with capacity of 400 l and greater .....</b>	<b>4</b>
<b>7.2.3</b>	<b>Venting of flexible tanks .....</b>	<b>4</b>
<b>8</b>	<b>Holding tanks .....</b>	<b>4</b>
<b>8.1</b>	<b>General requirements .....</b>	<b>4</b>
<b>8.1.1</b>	<b>Fastening .....</b>	<b>4</b>
<b>8.1.2</b>	<b>Indication of contents level .....</b>	<b>4</b>
<b>8.1.3</b>	<b>Accessibility of fittings and connections .....</b>	<b>4</b>
<b>8.1.4</b>	<b>Access opening .....</b>	<b>5</b>
<b>8.1.5</b>	<b>Tank walls .....</b>	<b>5</b>
<b>8.2</b>	<b>Requirements for permanently installed holding tanks .....</b>	<b>5</b>
<b>8.3</b>	<b>Requirements for portable holding tanks .....</b>	<b>5</b>
<b>9</b>	<b>Pump-outfitting .....</b>	<b>5</b>
<b>10</b>	<b>Identification .....</b>	<b>6</b>
<b>11</b>	<b>Information for owner's manual .....</b>	<b>6</b>
<b>Annex A (normative)</b>	<b>Nominal design of pump-outfitting .....</b>	<b>7</b>
<b>Annex B (informative)</b>	<b>Typical installations for toilet retention systems .....</b>	<b>9</b>