

# DIN EN ISO 12215-8:2019-09 (E)

**Small craft - Hull construction and scantlings - Part 8: Rudders (ISO 12215-8:2009 , including Cor 1:2010)**

---

## Contents

	Page
European foreword.....	5
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of Directive 2013/53/EU aimed to be covered .....	6
Foreword .....	7
Introduction .....	8
1 Scope .....	9
2 Normative references .....	9
3 Terms and definitions .....	9
4 Symbols.....	10
5 Design stresses.....	12
5.1 Rudder material .....	12
6 Rudder and steering arrangement, rudder types .....	13
6.1 General.....	13
6.1.1 General definition .....	13
6.1.2 Multi-rudder arrangement.....	13
6.1.3 Vertical support.....	13
6.1.4 Hard over stops.....	13
6.1.5 Actuating system of the rudder.....	14
6.1.6 Emergency tiller .....	14
6.2 Rudder types.....	14
6.2.1 Type I (spade) rudders (see Figures 1 and 2).....	14
6.2.2 Rudder spade with trapezoidal shape .....	15
6.2.3 Rudder types II to V (see Figure 3) .....	17
7 Design rudder force calculation .....	18
7.1 General.....	18
7.2 Force $F_1$ and corresponding load case .....	19
7.3 Force $F_2$ and corresponding load case .....	20
8 Rudder bending moment and reactions at bearings.....	21
8.1 General.....	21
8.2 Analysis of spade rudder (Type I) .....	21
8.2.1 Values of $k_b$ , bending moment $M$ and reactions at bearings for spade rudders (Type I).....	21
8.3 Analysis of skeg rudders (Types II to V) .....	22
8.3.1 General.....	22
8.3.2 Methods of calculation .....	22
8.3.3 Continuous beam theory .....	22
8.3.4 Simplified method.....	22
9 Rudder design torque, $T$ .....	24
10 Rudder and rudder stock design .....	25
10.1 Load bearing parts of the rudder .....	25
10.2 Metal rudder stock material .....	25

10.3	Design stress for metal rudder stock .....	26
10.4	Required diameter for solid circular metal rudder stocks .....	26
10.5	Vertical variation of the diameter of a Type I rudder (spade) .....	26
10.6	Round tubular stocks .....	27
10.7	Non-circular metal rudder stocks.....	28
10.8	Simple non-isotropic rudder stocks (e.g. wood or FRP).....	29
10.8.1	Blade acting both as rudder and rudder stock .....	29
10.8.2	Stress requirements for wood or plywood rudders.....	29
10.9	Complex structural rudders and rudder stocks in composite .....	29
10.10	Check of deflection of Type I rudder stocks between bearings .....	29
11	Equivalent diameter at the level of notches.....	30
12	Rudder bearings, pintles and gudgeons .....	30
12.1	Bearing arrangement.....	30
12.2	Clearance between stock and bearings .....	31
13	Rudder stock structure and rudder construction.....	32
13.1	Rudder stock structure.....	32
13.2	Rudder construction.....	32
13.3	FRP rudder blades .....	32
13.3.1	Blades with a core.....	32
13.3.2	Blade skins without internal core .....	33
13.4	Non-FRP rudder blades .....	33
14	Skeg structure .....	33
14.1	General .....	33
14.2	Design stress .....	33
	Annex A (normative) Metal for rudder stock.....	34
	Annex B (normative) Complex composite rudder stock design .....	38
	Annex C (normative) Complete calculation for rudders with skeg.....	40
	Annex D (informative) Geometrical properties of some typical rudder blade shapes .....	44
	Annex E (informative) Vertical variation of diameter for Type I rudders .....	47
	Annex F (informative) Type I rudders — Deflection of stock between bearings .....	49
	Bibliography .....	52

## Tables

Table 1 — Symbols, coefficients, parameters .....	11
Table 2 — Values of design stresses.....	12
Table 3 — Calculated values of $k_b$ for a trapezoidal spade as a function of $c_2/c_1$ .....	15
Table 4 — Rudder types and effective areas.....	17
Table 5 — Values of $r$ and $r_{\min}$ according to rudder type .....	25
Table 6 — Equivalent diameter $d$ .....	28
Table 7 — Computed recommended values of diametric clearance $D - d$ between stock and bushing .....	31
Table A.1 — Values of $\sigma_d$ for metallic rudder stocks .....	36
Table A.2 — Equivalence between stainless steel standard denominations .....	37

<b>Table D.1 — Values of <math>k_f</math> and <math>k_{f1}</math> for typical planform shapes.....</b>	<b>45</b>
<b>Table E.1 — Computed values for <math>\alpha = 1</math>, <math>\alpha = 0,75</math> and <math>\alpha = 0,5</math> .....</b>	<b>48</b>
<b>Table F.1 — Computed maximum values of <math>h_u/d</math> ratio and of <math>h_u</math> for <math>30 &lt; d &lt; 120</math> mm .....</b>	<b>51</b>

## Figures

<b>Figure 1 — Graphical determination of centroid, CS, of a trapeze .....</b>	<b>15</b>
<b>Figure 2 — Spade rudders: Type I.....</b>	<b>16</b>
<b>Figure 3 — Other rudder types: Types II to V.....</b>	<b>18</b>
<b>Figure 4 — Idealization for simplified method .....</b>	<b>23</b>
<b>Figure 5 — Variation of <math>d/d_{\max}</math> as a function of <math>h_{in}/h_u</math> or <math>h_{ou}/h_r</math>.....</b>	<b>27</b>
<b>Figure 6 — Determination of equivalent diameter at the level of key notches or square section.....</b>	<b>30</b>
<b>Figure C.1 — Rudder with a partial skeg.....</b>	<b>42</b>
<b>Figure C.2 — Rudder with a full skeg .....</b>	<b>43</b>
<b>Figure D.1 — Sketch of solid and hollowed rectangular or streamlined sections .....</b>	<b>44</b>