

ISO 19037:2019 (E)

Ships and marine technology — Gate valves for use in low temperature applications — Design and testing requirements

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Pressure-temperature rating
4.1	Types of fluids
4.2	Working pressure and design temperature
5	Design
5.1	General structure of a gate valve
5.2	Materials general
5.3	Types and materials of body
5.3.1	Types
5.3.2	Manufacturing
5.4	Design and materials of extended bonnet
5.4.1	Design
5.4.2	Materials
5.5	Design types and materials of wedge
5.5.1	Design
5.5.2	Materials
5.6	Types and materials of stem
5.6.1	Design
5.6.2	Materials
5.7	Stem sealing
5.8	Types and materials of a seat ring
5.8.1	Design
5.8.2	Materials
5.9	Types and materials of bolts and nuts
5.9.1	Design
5.9.2	Materials
5.10	Requirements of driving system and operating devices
5.11	Surface treatment
6	Welding heat treatment
6.1	Welding
6.2	Heat treatment
7	Test and inspection
7.1	Material test
7.2	Non-destructive inspection
7.2.1	Radiographic testing (RT)
7.2.2	Penetrant testing (PT)
7.2.3	Ultrasonic testing (UT)
7.2.4	Retest
7.3	Dimension check
7.4	Visual inspection
7.5	Heat treatment inspection
7.6	Operating tests
7.7	Pressure tests, back seat tests and leak tests

- 7.7.1 Pressure tests
- 7.7.2 Back seat tests
- 7.7.3 High-pressure pneumatic shell test
- 7.8 Fire safety test
- 7.9 Cryogenic tests
- 7.9.1 Scope of tests
- 7.9.2 Test procedure
- 7.9.2.1 Initial proving test
- 7.9.2.2 Cryogenic performance tests
- 7.9.2.3 Returning ambient temperature test
- 7.9.2.4 Disassembly inspection
- 7.9.2.5 Final leakage test and back seat test
- 7.9.3 Submission of test result

8 Marking

Annex A (informative) Cryogenic gate valve — Example

Page count: 16