ISO 11336-3:2019 (E)

Large yachts — Strength, weathertightness and watertightness of glazed openings — Part 3: Quality assurance, installation and in-service inspection

Contents

Foreword

1 Scope

2 Normative references

3 Terms and definitions

4 Requirements for glazing material products

- 4.1 Product data sheet
- 4.1.1 General
- 4.1.2 Data to be provided for all glazing materials
- 4.1.3 Data to be provided for monolithic glazing materials and monolithic glazing components
- 4.1.4 Data to be provided for laminated safety glass and for compound glazing materials
- 4.1.5 Insulated glazing units
- 4.2 Detailed description of the properties
- 4.2.1 Mechanical properties
- 4.2.1.1 Mechanical properties to be specified
- 4.2.1.2 Methods to derive mechanical properties of the product
- 4.2.2 Post failure behaviour
- 4.3 Dangerous substances
- 4.4 Durability
- 4.5 Suitability for application on control positions

5 Evaluation of conformity

- 5.1 General
- 5.2 Initial examination
- 5.3 Factory production control

6 Marking and/or labelling

- 6.1 General
- 6.2 Product marking
- 6.3 Product records

7 Information to be provided to the vessel

8 Inspection during installation

9 Lifetime inspections

- 9.1 General
- 9.2 Inspections
- 9.3 Inspection of glazing
- 9.3.1 General
- 9.3.2 Inspection of glazing containing TTG
- 9.3.3 Inspection of glazing containing CSG
- 9.3.4 Inspection of laminated glazing and glazing with materials other than glass
- 9.4 Inspection of bonding
- 9.5 Durability of materials
- 9.6 Routine inspections
- 9.6.1 Signs of deterioration
- 9.6.2 Signs of malfunctioning
- 9.7 Further investigation

9.8 Replacement or renewal of bonding and sealing.

Annex A (normative) Tests for ensuring conformity

A.1 Testing other than in EN 14449

Annex B (informative) Laminated safety glass: Mechanical resistance tests

B.1 General
B.2 4-point bending strength test to determine the characteristic failure strength of glazing materials
B.3 Factory acceptance test without breakage
B.3.1 General
B.3.2 Test for complete laminate
B.3.3 Alternative method to test interlayer only
B.3.4 Test rig setup
B.3.5 Typical execution of test
B.4 Other test methods
B.4.1 General
B.4.2 Compressive shear test
B.4.3 Pummel test
B.4.4 Tenacity and adhesion test for determination of link between product and impact performance, i.e. EN 356, EN 12600

Annex C (informative) Criteria for deciding if a change within an assembly requires a new initial type test

C.1 General

Annex D (informative) Background notes on certain clauses in this document

D.1 Subclause 4.1.3: Horizontal or vertical process for TTG
D.2 Subclause 4.1.4: Use of annealed glass (AG)
D.3 Terms 3.3 and 3.6: Product description versus product data sheet
D.4 Subclause 9.3.2: Risks associated with edge damage in TTG glazing
D.5 Subclause 9.3.3: Risks associated with surface or edge damage in CSG glazing
D.6 Terms 3.12 to 3.14: Lines L1 to L3 describing levels above the design waterline
D.7 Clause 8: Table 2, positions on board

Annex E (informative) Application of the Weibull distribution

Annex F (normative) Information to be supplied to the vessel

Annex G (informative) Example of bonding record

Annex H (informative) Example of inspection record

Page count: 30