

ISO 25862:2019 (E)

Ships and marine technology — Marine magnetic compasses, binnacles and azimuth reading devices

Contents

| | |
|---------|---|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Magnetic compasses |
| 4.1 | General |
| 4.1.1 | Class A magnetic compass |
| 4.1.2 | Class B magnetic compass |
| 4.2 | Construction and materials |
| 4.2.1 | Magnetic material |
| 4.2.2 | Lubber mark |
| 4.2.3 | Position of the card (class A only) |
| 4.2.4 | Angle of gimbal axes and intersection of vertical planes passing through them |
| 4.2.5 | Thickness of the top glass cover (class A only) |
| 4.2.6 | Constructional condition within the temperature range |
| 4.2.7 | Horizontal position |
| 4.3 | Mounting |
| 4.3.1 | Tilt of supporting device |
| 4.3.2 | Freedom of the compass card with no supporting gimbal |
| 4.4 | Directional system |
| 4.4.1 | Moment of inertia |
| 4.4.2 | Suspension (class A only) |
| 4.4.3 | Magnetic moment |
| 4.4.4 | Settling time |
| 4.4.5 | Tilt of the directional system with regard to the vertical field (class A only) |
| 4.4.6 | Supporting force (class A only) |
| 4.5 | Compass card |
| 4.5.1 | Graduation |
| 4.5.2 | Diameter of the card |
| 4.5.3 | Readability |
| 4.5.4 | Bearing compasses |
| 4.6 | Accuracy |
| 4.6.1 | Directional error |
| 4.6.2 | Error of lubber marks |
| 4.6.3 | Error due to friction |
| 4.6.4 | Swirl error |
| 4.6.5 | Induction error (class A only) |
| 4.6.6 | Mounting error of azimuth reading device |
| 4.6.7 | Error due to eccentricity of the verge ring (class A only) |
| 4.7 | Environmental conditions tests of magnetic compasses (class A only) |
| 5 | Binnacles |
| 5.1 | General |
| 5.2 | Binnacle type A1 |
| 5.2.1 | General |
| 5.2.2 | Construction and materials |
| 5.2.3 | Provision for correction of deviation (if combined with class B compasses) |
| 5.2.3.1 | Material |
| 5.2.3.2 | Compensation for horizontal permanent magnetism |

| | |
|---------|---|
| 5.2.3.3 | Correction for heeling error |
| 5.2.3.4 | Compensation for horizontal induced fields due to the horizontal component of the Earth's magnetic field in the soft iron in a ship |
| 5.2.3.5 | Compensation for horizontal induced fields due to the vertical component of the Earth's magnetic field in the soft iron in a ship |
| 5.2.3.6 | Positions and attachment of correcting devices |
| 5.2.3.7 | Corrector coils |
| 5.2.4 | Accuracy of fore and aft marks |
| 5.2.5 | Illumination |
| 5.2.6 | Environmental conditions requirements (class A only) |
| 5.3 | Binnacle type A2 |
| 5.3.1 | General |
| 5.3.2 | Construction and materials |
| 5.3.3 | Provision for correction of deviation |
| 5.3.3.1 | Material |
| 5.3.3.2 | Compensation for horizontal permanent magnetism |
| 5.3.3.3 | Correction for heeling error |
| 5.3.3.4 | Compensation for horizontal induced fields due to the horizontal component of the Earth's magnetic field in the soft iron of the ship |
| 5.3.3.5 | Compensation for horizontal induced fields due to the vertical component of the Earth's magnetic field in the soft iron of the ship |
| 5.3.3.6 | Attachment of correcting devices |
| 5.3.4 | Accuracy of fore and aft marks |
| 5.3.5 | Illumination |
| 5.3.6 | Environmental conditions requirements (class A only) |
| 6 | Azimuth reading devices |
| 6.1 | General |
| 6.2 | Azimuth sight |
| 6.3 | Azimuth reading devices with vanes |
| 6.4 | Level |
| 7 | Marking |
| 8 | Designation |
| Annex A | (normative) Testing and certification of marine magnetic compasses, binnacles and azimuth reading devices — General requirements |
| A.1 | Introduction |
| A.2 | Scope of testing |
| A.3 | Types of compasses to be tested |
| A.4 | Test conditions |
| A.5 | Certification |
| Annex B | (normative) Testing and certification of marine magnetic compasses |
| B.1 | Manufacturer's statement |
| B.2 | Marking |
| B.3 | Compass and gimbaling checks and tests |
| B.3.1 | Construction and material |
| B.3.1.1 | Condition of compass bowl |
| B.3.1.2 | Non-magnetic properties (type-test only) |
| B.3.1.3 | Condition at high temperature |
| B.3.1.4 | Condition at low temperature |
| B.3.1.5 | Thickness of top and bottom glass covers (type-test only) |
| B.3.1.6 | Heading transmitting system |
| B.3.2 | Compass gimbaling |
| B.3.2.1 | Plane of gimbal axes (type-test only) |
| B.3.2.2 | Angle of gimbal axes and intersection of vertical planes passing through them (type-test only) |
| B.3.2.3 | Freedom of movement within gimbal ring |
| B.3.2.4 | Horizontal position |
| B.3.2.5 | Friction of inner gimbal axis |
| B.3.2.6 | Inner and outer gimbal bearings (type-test only) |
| B.3.3 | Compass bowl |

- B.3.3.1 Relative verge ring graduation (if any)
- B.3.3.2 Error due to eccentricity of verge ring graduation (if any verge ring graduation)
- B.3.3.3 Accuracy of centring of azimuth reading device (type-test only)
- B.3.4 Compass card bearing
 - B.3.4.1 Height of pivot bearing (type-test only)
 - B.3.4.2 Protection of directional system against displacement
 - B.3.4.3 Freedom of tilt of directional system
- B.3.5 Lubber marks
 - B.3.5.1 Number of lubber marks
 - B.3.5.2 Visibility of lubber mark(s)
 - B.3.5.3 Width of lubber mark(s)
 - B.3.5.4 Distance between lubber mark(s) and card outer edge
- B.3.6 Directional system
 - B.3.6.1 Compass card
 - B.3.6.1.1 Graduation
 - B.3.6.1.2 Diameter of the card
 - B.3.6.1.3 Readability
 - B.3.6.1.4 Relationship of edge of compass card and pivot bearing (type-test only)
 - B.3.6.2 Directional system magnets
 - B.3.6.2.1 Magnetic moment
 - B.3.6.2.2 Induction error (type-test only)
 - B.3.6.2.3 Coercivity (type-test only)
 - B.3.6.2.4 Change in tilt when vertical flux density has changed (type-test only)
 - B.3.6.3 Settling time
- B.3.7 Accuracy
 - B.3.7.1 Directional error
 - B.3.7.2 Error of lubber marks
 - B.3.7.3 Error due to friction
 - B.3.7.4 Swirl error
 - B.3.7.5 Environmental condition test of magnetic compasses (class A only) (type-test only)
- B.4 Test certificate

Annex C (normative) Testing and certification of azimuth reading devices

- C.1 General
 - C.1.1 Groups of azimuth devices to be tested
 - C.1.2 Manufacturer's statement for azimuth reading devices
- C.2 Azimuth reading device checks and tests
 - C.2.1 Material
 - C.2.2 Mounting upon compass
 - C.2.3 Adjustment of spirit level
 - C.2.4 Field of view and range of altitude (type-test only)
 - C.2.5 Accuracy
 - C.2.5.1 Sights or telescope-sights (group I)
 - C.2.5.1.1 Parallelism of vanes
 - C.2.5.1.2 Perpendicularity of vanes upon base
 - C.2.5.1.3 Attachment and adjustment of observation mirror
 - C.2.5.1.4 Freedom of distortion of mirror and shades
 - C.2.5.1.5 Prismatic magnifying glass (if any)
 - C.2.5.2 Azimuth mirror or prism instruments such as Thomson type (group II)
 - C.2.5.2.1 Construction
 - C.2.5.2.2 Focal length of lens
 - C.2.5.2.3 Error caused by mechanical inaccuracy
 - C.2.5.2.3.1 Prism axis not at right angles to line of sight
 - C.2.5.2.3.2 Prism axis not parallel to plane of compass top glass
 - C.2.5.2.4 Card diameter
 - C.2.5.2.5 Error in shades of azimuth mirror
 - C.2.5.2.6 Level
 - C.2.6 Shadow pin (if any)
 - C.2.7 Pelorus
- C.3 Test certificate

Annex D (normative) Type-testing and certification of binnacles

- D.1 General
 - D.1.1 Overview

- D.1.2 Binnacles and correcting devices to be tested
 - D.1.3 Manufacturer's statement for binnacles
 - D.2 Binnacles
 - D.2.1 Construction and material
 - D.2.1.1 Dimensions
 - D.2.1.2 Non-magnetic properties
 - D.2.2 Compass suspension
 - D.2.2.1 Outer gimbal axis
 - D.2.2.2 Tilt of supporting device
 - D.2.2.3 Precautions against dislodging
 - D.2.2.4 Friction of gimbal and compass axes
 - D.2.2.5 Play in outer gimbal axis bearing
 - D.2.2.6 Compass suspensions provided with springs
 - D.2.2.6.1 Horizontal movement of compass bowl and gimbaling
 - D.2.2.6.2 Effect of azimuth reading device
 - D.2.3 Provisions to correct misalignment
 - D.2.4 Correcting devices, marking, coercivity and securing (type A1 binnacles and, if fitted, type A2 binnacles)
 - D.2.4.1 General
 - D.2.4.2 Heeling error corrector magnets
 - D.2.4.3 Mounting of horizontal corrector magnets
 - D.2.4.3.1 Error of alignment
 - D.2.4.3.2 Position error
 - D.2.4.3.3 Minimum distance of horizontal correcting magnets from directional system and their strength
 - D.2.4.4 Attachment of quadrantal correctors
 - D.2.4.5 Flinders' bar
 - D.2.5 Corrector coils
 - D.2.6 Illumination
 - D.2.6.1 General
 - D.2.6.2 Magnetic influence of lamps, plugs, sockets, switches, dimmers and wiring
 - D.2.6.3 Readability of reflector and projector compasses
 - D.2.6.4 Environmental condition test of binnacle (class A only) (type-test only)
- D.3 Test certificate

Annex E (normative) Positioning of magnetic compasses in ships

- E.1 General
- E.2 General
 - E.2.1 Compass positions
 - E.2.2 Safe distances
 - E.2.3 Accuracy of magnetic compasses
 - E.2.4 Functions of magnetic compasses
- E.3 Minimum distance requirements concerning the ship's structure
- E.4 Safe-distance requirements for magnetic and electrical equipment and electric cables

Annex F (normative) Determination of safe distances

Annex G (normative) Adjustment of magnetic compass deviation

- G.1 General
- G.2 When to adjust compass
- G.3 Compass adjusters
- G.4 Adjustment by Flinders' bars
- G.5 Means to correct the heading to a true heading
- G.6 Description of the adjustment
- G.7 Deviation table or curve

Annex H (normative) Requirements of magnetic compass for lifeboats/rescue boats

- H.1 General
- H.2 Requirements of magnetic compass for lifeboats/rescue boats
 - H.2.1 General
 - H.2.2 Diameter of the card
 - H.2.3 Width of lubber mark(s)
 - H.2.4 Environmental conditions test of magnetic compasses