

ISO 21963:2020 (E)

Ships and marine technology — Marine environment protection — Tanks and piping systems for facilitating 5 ppm oil-water separation

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Technical specifications |
| 4.1 | Oil-water separation equipment (OWSE) |
| 4.2 | 5 ppm OWS |
| 4.3 | Oil content meter (OCM) |
| 4.4 | Automatic discharge stopping device (ADSD) |
| 4.5 | Electric and electronic systems |
| 4.6 | Heating facilities |
| 5 | Installation requirements |
| 5.1 | 5 ppm OWS |
| 5.2 | Oil content meter (OCM) |
| 5.3 | Automatic discharge stopping device (ADSD) |
| 6 | Testing of the 5 ppm OWS |
| Annex A | (informative) Examples of schematic diagrams for the management of oil/water effluents on fixed offshore marine structures |
| Annex B | (normative) Testing of 5 ppm OWS |
| B.1 | General |
| B.2 | Test rig, equipment and arrangement |
| B.2.1 | General |
| B.2.2 | Test tanks |
| B.2.3 | Flow meters |
| B.2.4 | Pumps |
| B.2.4.1 | Centrifugal pumps |
| B.2.4.2 | Integrated feed pump |
| B.2.5 | Conditioning pipe |
| B.2.6 | OWS sampling arrangement |
| B.3 | Test fluids |
| B.3.1 | General |
| B.3.2 | Test fluid "A" |
| B.3.3 | Test fluid "B" |
| B.3.4 | Test fluid "C" |
| B.4 | Test procedures |
| B.4.1 | General |
| B.4.2 | Test with test fluid "A" |
| B.4.3 | Test with test fluid "B" |
| B.4.4 | Tests with test fluid "C" |
| B.5 | Analysis |
| B.6 | Reporting |
| Annex C | (normative) Environmental testing for the switchboard of the OWSE |

| | |
|----------------|--|
| C.1 | General |
| C.2 | Test specification |
| C.2.1 | Testing requirements |
| C.2.2 | Test specification details |
| C.2.2.1 | General specification |
| C.2.2.2 | Vibration test |
| C.2.2.3 | Temperature test |
| C.2.2.4 | Humidity test |
| C.2.2.5 | Inclination test for OWS installed on ships |

Page count: 20