

# ISO 22013:2021 (E)

## Marine environment sensor performance — Specifications, testing and reporting — General requirements

---

### Contents

|         |   |
|---------|---|
|         | Foreword  |
|         | Introduction                                    |
| 1       | Scope   |
| 2       | Normative references                            |
| 3       | Terms and definitions                           |
| 4       | Specifications                                  |
| 4.1     | General   |
| 4.2     | Calibration                                     |
| 4.3     | Range   |
| 4.3.1   | Calibrated range                                |
| 4.3.2   | Measuring range                                 |
| 4.3.3   | Maximum range                                   |
| 4.4     | Accuracy  |
| 4.5     | Resolution                                      |
| 4.6     | Response time                                   |
| 4.7     | Depth and pressure                              |
| 4.7.1   | Maximum depth rating                            |
| 4.7.2   | Crush depth rating                              |
| 4.8     | Sample rate                                     |
| 4.9     | Mechanical                                      |
| 4.9.1   | Wetted materials                                |
| 4.9.2   | Exterior dimensions                             |
| 4.9.3   | Mass or weight in air                           |
| 4.9.4   | Weight in freshwater                            |
| 4.9.5   | Weight in seawater                              |
| 4.9.6   | Operating temperature range                     |
| 4.10    | Electrical                                      |
| 4.10.1  | Input voltage range                             |
| 4.10.2  | Operating power consumption                     |
| 4.10.3  | Startup power consumption                       |
| 4.11    | Interface                                       |
| 4.11.1  | Electrical connections                          |
| 4.11.2  | Communications protocol                         |
| 4.12    | Stability                                       |
| 4.13    | Shelf-life                                      |
| 5       | Test methods                                    |
| 5.1     | Overview  |
| 5.2     | General experimental design                     |
| 5.2.1   | General   |
| 5.2.2   | Sensor settings                                 |
| 5.2.3   | Reference                                       |
| 5.2.4   | Re-calibration                                  |
| 5.3     | Calibration                                     |
| 5.3.1   | General   |
| 5.3.2   | Calibration method                              |
| 5.3.3   | Experimental design — Layout of the calibration |
| 5.3.3.1 | Number of levels and calibrated range           |

|         |  |
|---------|--|
| 5.3.3.2 | Reference  |
| 5.3.4   | Calibration curve  |
| 5.3.5   | Post-calibration operations                              |
| 5.4     | Accuracy   |
| 5.4.1   | General  |
| 5.4.2   | Modifications to ISO 5725                                |
| 5.4.2.1 | General  |
| 5.4.2.2 | Inter-sensor variability                                 |
| 5.4.3   | Statistical model  |
| 5.4.4   | Determination of precision                               |
| 5.4.4.1 | General  |
| 5.4.4.2 | Repeatability conditions                                 |
| 5.4.4.3 | Reproducibility conditions                               |
| 5.4.5   | Experimental design — Layout of the precision experiment |
| 5.4.5.1 | Number of sensors  |
| 5.4.5.2 | Number of levels and range                               |
| 5.4.5.3 | Environmental conditions                                 |
| 5.4.5.4 | Number of replicates                                     |
| 5.4.5.5 | Calibration of sensors                                   |
| 5.4.6   | Reference  |
| 5.4.7   | Determination of trueness (bias)                         |
| 5.4.8   | Statistical analysis                                     |
| 5.4.8.1 | Precision  |
| 5.4.8.2 | Trueness   |
| 5.5     | Resolution   |
| 5.5.1   | General  |
| 5.5.2   | Experimental design                                      |
| 5.5.3   | Calculation of $s$ noise                                 |
| 5.5.4   | Calculation of $s$ noise $ij$                            |
| 5.6     | Response time  |
| 5.6.1   | General  |
| 5.6.2   | Experimental design                                      |
| 5.6.2.1 | General  |
| 5.6.2.2 | Medium   |
| 5.6.2.3 | Sample period  |
| 5.6.2.4 | Flow   |
| 5.6.2.5 | Step change  |
| 5.6.3   | Response curve   |
| 5.6.3.1 | General  |
| 5.6.3.2 | Determination of the response curve                      |
| 5.6.3.3 | Determination without experiment                         |
| 5.6.3.4 | Calculation of $t_{63}$                                  |
| 5.7     | Depth and pressure                                       |
| 5.7.1   | Maximum depth rating                                     |
| 5.7.2   | Crush depth rating                                       |
| 5.7.3   | Pressure case void                                       |
| 5.8     | Mechanical   |
| 5.8.1   | Wetted materials   |
| 5.8.2   | Weight in freshwater                                     |
| 5.8.3   | Weight in seawater                                       |
| 5.8.4   | Operating temperature range                              |
| 5.9     | Electrical   |
| 5.9.1   | Input voltage range                                      |
| 5.9.2   | Operating power consumption                              |
| 5.9.3   | Startup power consumption                                |
| 5.10    | Interface  |
| 5.10.1  | General  |
| 5.10.2  | Power on/standby   |
| 5.10.3  | Galvanic isolation test                                  |
| 5.11    | Stability  |
| 5.11.1  | General  |
| 5.11.2  | Experimental design                                      |
| 5.11.3  | Calculation of $d$                                       |
| 5.11.4  | Field stability  |

- 5.11.4.1 General
- 5.11.4.2 Guidelines on determination
- 5.11.4.3 Publication
- 5.12 Shelf-life
- 5.12.1 General
- 5.12.2 Experimental design
- 5.12.3 Calculation of d

**6 Publication**

- 6.1 General
- 6.2 Data sheets
- 6.2.1 General
- 6.2.2 Test reports
- 6.3 Calibration certificates

**Annex A (informative) Determination of the accuracy (precision and trueness) — Example**

- A.1 Description
- A.2 Precision assessment
  - A.2.1 Cell means
  - A.2.2 Computation of standard deviations
  - A.2.3 Scrutiny for consistency and outliers
  - A.2.4 Computation of  $s_{rj}$ ,  $s_{Rj}$
  - A.2.5 Dependence of precision on m
  - A.2.6 Conclusions
- A.3 Trueness assessment
  - A.3.1 Estimation of the bias
  - A.3.2 Variation of the bias
  - A.3.3 95 % confidence interval for the bias
  - A.3.4 Significance of the bias
  - A.3.5 Conclusion

**Annex B (informative) Determination of the response time — Examples**

- B.1 Example determination of response time for a sound velocity sensor
  - B.1.1 Description
  - B.1.2 Developing the model
  - B.1.3 Calculation of  $t_{63}$
  - B.1.4 Conclusion
- B.2 Example determination of the response time for a dissolved carbon dioxide sensor
  - B.2.1 Description
  - B.2.2 Scrutiny of the step experiment
    - B.2.2.1 Sample period
    - B.2.2.2 Speed
    - B.2.2.3 Levels
    - B.2.2.4 Continuity
    - B.2.2.5 Flow
  - B.2.3 Results
  - B.2.4 Rising step
  - B.2.5 Calculation of  $t_{63}$
  - B.2.6 Conclusion

**Annex C (informative) Data sheet for a sound velocity sensor — Example**