

ISO 22013:2021 (E)

Marine environment sensor performance — Specifications, testing and reporting — General requirements

Contents

| | |
|---------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Specifications |
| 4.1 | General |
| 4.2 | Calibration |
| 4.3 | Range |
| 4.3.1 | Calibrated range |
| 4.3.2 | Measuring range |
| 4.3.3 | Maximum range |
| 4.4 | Accuracy |
| 4.5 | Resolution |
| 4.6 | Response time |
| 4.7 | Depth and pressure |
| 4.7.1 | Maximum depth rating |
| 4.7.2 | Crush depth rating |
| 4.8 | Sample rate |
| 4.9 | Mechanical |
| 4.9.1 | Wetted materials |
| 4.9.2 | Exterior dimensions |
| 4.9.3 | Mass or weight in air |
| 4.9.4 | Weight in freshwater |
| 4.9.5 | Weight in seawater |
| 4.9.6 | Operating temperature range |
| 4.10 | Electrical |
| 4.10.1 | Input voltage range |
| 4.10.2 | Operating power consumption |
| 4.10.3 | Startup power consumption |
| 4.11 | Interface |
| 4.11.1 | Electrical connections |
| 4.11.2 | Communications protocol |
| 4.12 | Stability |
| 4.13 | Shelf-life |
| 5 | Test methods |
| 5.1 | Overview |
| 5.2 | General experimental design |
| 5.2.1 | General |
| 5.2.2 | Sensor settings |
| 5.2.3 | Reference |
| 5.2.4 | Re-calibration |
| 5.3 | Calibration |
| 5.3.1 | General |
| 5.3.2 | Calibration method |
| 5.3.3 | Experimental design — Layout of the calibration |
| 5.3.3.1 | Number of levels and calibrated range |

| | |
|---------|--|
| 5.3.3.2 | Reference |
| 5.3.4 | Calibration curve |
| 5.3.5 | Post-calibration operations |
| 5.4 | Accuracy |
| 5.4.1 | General |
| 5.4.2 | Modifications to ISO 5725 |
| 5.4.2.1 | General |
| 5.4.2.2 | Inter-sensor variability |
| 5.4.3 | Statistical model |
| 5.4.4 | Determination of precision |
| 5.4.4.1 | General |
| 5.4.4.2 | Repeatability conditions |
| 5.4.4.3 | Reproducibility conditions |
| 5.4.5 | Experimental design — Layout of the precision experiment |
| 5.4.5.1 | Number of sensors |
| 5.4.5.2 | Number of levels and range |
| 5.4.5.3 | Environmental conditions |
| 5.4.5.4 | Number of replicates |
| 5.4.5.5 | Calibration of sensors |
| 5.4.6 | Reference |
| 5.4.7 | Determination of trueness (bias) |
| 5.4.8 | Statistical analysis |
| 5.4.8.1 | Precision |
| 5.4.8.2 | Trueness |
| 5.5 | Resolution |
| 5.5.1 | General |
| 5.5.2 | Experimental design |
| 5.5.3 | Calculation of s noise |
| 5.5.4 | Calculation of s noise ij |
| 5.6 | Response time |
| 5.6.1 | General |
| 5.6.2 | Experimental design |
| 5.6.2.1 | General |
| 5.6.2.2 | Medium |
| 5.6.2.3 | Sample period |
| 5.6.2.4 | Flow |
| 5.6.2.5 | Step change |
| 5.6.3 | Response curve |
| 5.6.3.1 | General |
| 5.6.3.2 | Determination of the response curve |
| 5.6.3.3 | Determination without experiment |
| 5.6.3.4 | Calculation of t_{63} |
| 5.7 | Depth and pressure |
| 5.7.1 | Maximum depth rating |
| 5.7.2 | Crush depth rating |
| 5.7.3 | Pressure case void |
| 5.8 | Mechanical |
| 5.8.1 | Wetted materials |
| 5.8.2 | Weight in freshwater |
| 5.8.3 | Weight in seawater |
| 5.8.4 | Operating temperature range |
| 5.9 | Electrical |
| 5.9.1 | Input voltage range |
| 5.9.2 | Operating power consumption |
| 5.9.3 | Startup power consumption |
| 5.10 | Interface |
| 5.10.1 | General |
| 5.10.2 | Power on/standby |
| 5.10.3 | Galvanic isolation test |
| 5.11 | Stability |
| 5.11.1 | General |
| 5.11.2 | Experimental design |
| 5.11.3 | Calculation of d |
| 5.11.4 | Field stability |

- 5.11.4.1 General
- 5.11.4.2 Guidelines on determination
- 5.11.4.3 Publication
- 5.12 Shelf-life
- 5.12.1 General
- 5.12.2 Experimental design
- 5.12.3 Calculation of d

6 Publication

- 6.1 General
- 6.2 Data sheets
- 6.2.1 General
- 6.2.2 Test reports
- 6.3 Calibration certificates

Annex A (informative) Determination of the accuracy (precision and trueness) — Example

- A.1 Description
- A.2 Precision assessment
 - A.2.1 Cell means
 - A.2.2 Computation of standard deviations
 - A.2.3 Scrutiny for consistency and outliers
 - A.2.4 Computation of s_{rj} , s_{Rj}
 - A.2.5 Dependence of precision on m
 - A.2.6 Conclusions
- A.3 Trueness assessment
 - A.3.1 Estimation of the bias
 - A.3.2 Variation of the bias
 - A.3.3 95 % confidence interval for the bias
 - A.3.4 Significance of the bias
 - A.3.5 Conclusion

Annex B (informative) Determination of the response time — Examples

- B.1 Example determination of response time for a sound velocity sensor
 - B.1.1 Description
 - B.1.2 Developing the model
 - B.1.3 Calculation of t_{63}
 - B.1.4 Conclusion
- B.2 Example determination of the response time for a dissolved carbon dioxide sensor
 - B.2.1 Description
 - B.2.2 Scrutiny of the step experiment
 - B.2.2.1 Sample period
 - B.2.2.2 Speed
 - B.2.2.3 Levels
 - B.2.2.4 Continuity
 - B.2.2.5 Flow
 - B.2.3 Results
 - B.2.4 Rising step
 - B.2.5 Calculation of t_{63}
 - B.2.6 Conclusion

Annex C (informative) Data sheet for a sound velocity sensor — Example