

ISO 9650-1:2022-05 (E)

Small craft - Inflatable liferafts - Part 1: Type 1 and type 2

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | iv |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | General provisions | 2 |
| 4.1 | General | 2 |
| 4.2 | Types of liferaft | 3 |
| 5 | Requirements | 3 |
| 5.1 | General requirements | 3 |
| 5.2 | Detailed requirements | 4 |
| 5.2.1 | Deployment | 4 |
| 5.2.2 | Inflation | 5 |
| 5.2.3 | Buoyancy | 6 |
| 5.2.4 | Stability and performance at sea | 7 |
| 5.2.5 | Solidity, watertightness, materials | 8 |
| 5.2.6 | Habitability | 9 |
| 5.2.7 | Visibility to rescuers | 10 |
| 5.2.8 | Fittings and equipment | 11 |
| 5.2.9 | Instructions and marking | 14 |
| 5.2.10 | Packaging | 16 |
| 6 | Testing | 16 |
| 6.1 | General | 16 |
| 6.2 | Launching (drop) test | 17 |
| 6.3 | Inflation tests under temperature | 18 |
| 6.3.1 | General | 18 |
| 6.3.2 | Ambient-temperature test | 18 |
| 6.3.3 | High-temperature test | 18 |
| 6.3.4 | Low-temperature test | 18 |
| 6.4 | Testing of stabilization means | 19 |
| 6.5 | Righting test | 19 |
| 6.6 | Boarding test | 19 |
| 6.7 | Towing test with sea anchor deployed | 19 |
| 6.8 | Pressure test | 20 |
| 6.8.1 | Buoyancy chambers and canopy support | 20 |
| 6.8.2 | Inflatable floor (if fitted) | 20 |
| 6.9 | Canopy watertightness test | 20 |
| 6.10 | Visual inspection of the protective outer container | 21 |
| 6.11 | Visual inspection of the liferaft | 21 |
| 6.12 | Equipment | 21 |
| 6.13 | Pressure relief valve test | 21 |
| 6.14 | Lights and batteries test | 21 |
| 6.15 | Mooring out test | 21 |
| 6.16 | Float free buoyancy test | 21 |

| | | |
|----------|---------------------------|-----------|
| 7 | Servicing | 22 |
| | Bibliography | 23 |