

ISO 12217-2:2022-12 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 2: Sailing boats of hull length greater than or equal to 6 m

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
3.1	Primary	2
3.2	Hazards	4
3.3	Downflooding	4
3.4	Dimensions, areas and angles	5
3.5	Condition, mass and volume	6
3.6	Other terms and definitions	9
4	Symbols	12
5	Procedure	13
5.1	Maximum load	13
5.2	Sailing or non-sailing	13
5.3	Tests, calculations and requirements to be applied	13
5.4	Variation in input parameters	14
6	Requirements for monohull boats	14
6.1	Requirements to be applied	14
6.2	Downflooding	15
6.2.1	Downflooding openings	15
6.2.2	Downflooding height	18
6.2.3	Downflooding angle	19
6.3	Recess size	19
6.3.1	Application	19
6.3.2	Simplified methods	20
6.3.3	Direct calculation method	22
6.4	Minimum righting energy	22
6.5	Angle of vanishing stability	23
6.5.1	General	23
6.5.2	Normal requirement	23
6.5.3	Alternative requirement for design category B	23
6.6	Stability index (STIX)	24
6.6.1	Method	24
6.6.2	Dynamic stability factor (FDS)	25
6.6.3	Inversion recovery factor (FIR)	25
6.6.4	Knockdown recovery factor (FKR)	25
6.6.5	Displacement-length factor (FDL)	26
6.6.6	Beam-displacement factor (FBD)	26
6.6.7	Wind moment factor (FWM)	26
6.6.8	Downflooding factor (FDF)	27
6.6.9	Calculation of the stability index (STIX)	27
6.7	Knockdown-recovery test	27
6.8	Wind stiffness test	28

6.8.1	General	28
6.8.2	Practical test	28
6.8.3	Compliance by calculation	30
6.8.4	Requirements	31
6.9	Flotation requirements	32
6.10	Capsize-recovery test	32
6.11	Detection and removal of water	34
7	Requirements for catamarans, trimarans and form-stable monohulls	35
7.1	Requirements to be applied	35
7.2	Downflooding openings	35
7.3	Downflooding height	35
7.4	Recess size	35
7.5	Stability information	35
7.6	Safety signs	36
7.7	Bare poles factor	37
7.8	Rolling in breaking waves	37
7.9	Pitchpoling	38
7.10	Diagonal stability	38
7.11	Habitable multihull boats	38
7.12	Buoyancy when inverted	40
7.13	Escape after inversion	41
8	Safety signs	42
9	Application	42
9.1	Deciding the design category	42
9.2	Meaning of the design categories	42
Annex A (normative) Full method for required downflooding height		44
Annex B (normative) Methods for calculating downflooding angle		46
Annex C (normative) Determining the curve of righting moments		48
Annex D (normative) Method for calculating reserve of buoyancy after inversion or swamping		51
Annex E (normative) Flotation material and elements		53
Annex F (normative) Information for the craft's owner's manual		55
Annex G (normative) Determination of safe wind speed information		59
Annex H (normative) Determination of longitudinal righting characteristics		62
Annex I (informative) Summary of requirements		65
Annex J (informative) Worksheets		68
Annex K (informative) Illustration of recess retention level		87
Bibliography		88