

# ISO 24482:2023-03 (E)

## Large yachts - Navigational bridge visibility

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Bridge construction .....</b>	<b>3</b>
4.1	Bridge position .....	3
4.2	Lower edge of front windows .....	4
4.3	Upper edge of front windows .....	4
4.4	Upper edge of navigational consoles .....	4
4.5	Inclination of windows .....	4
4.6	Curved windows .....	5
4.7	Window breadth .....	5
4.8	Framing of windows .....	6
4.8.1	General .....	6
4.8.2	Frame insulation .....	6
4.8.3	Maximum frame size .....	6
4.9	Window tinting .....	6
4.10	Clear view .....	6
4.11	Removable sunscreens .....	7
4.12	Working positions .....	7
4.13	Bridge wings .....	7
<b>5</b>	<b>Navigational bridge visibility .....</b>	<b>7</b>
5.1	Typical bridge arrangement .....	7
5.2	Position of the eye .....	8
5.3	View of the sea surface .....	8
5.4	Horizontal field of vision .....	8
5.5	Vertical field of vision .....	9
5.5.1	Vertical field of vision from the conning position above the horizontal plane .....	9
5.5.2	Vertical field of vision from the conning position below the horizontal plane .....	9
5.6	Blind sectors .....	9
5.7	Clear sector .....	13
5.8	Field of vision from the docking position .....	13
<b>6</b>	<b>Test procedure .....</b>	<b>14</b>
6.1	General .....	14
6.2	Design stage .....	14
6.3	Harbour acceptance test .....	15
6.4	Tests for optical properties of the glass .....	15
Bibliography .....		16