ISO 24482:2023-03 (E)

Large yachts - Navigational bridge visibility

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Bridge construction 3
4.1 Bridge position 3
4.2 Lower edge of front windows 4
4.3 Upper edge of front windows 4
4.4 Upper edge of navigational consoles 4
4.5 Inclination of windows 4
4.6 Curved windows 5
4.7 Window breadth 5
4.8 Framing of windows 6
4.8.1 General 6
4.8.2 Frame insulation 6
4.8.3 Maximum frame size 6
4.9 Window tinting 6
4.10 Clear view 6
4.11 Removable sunscreens 7
4.12 Working positions 7
4.13 Bridge wings 7

5 Navigational bridge visibility 7
5.1 Typical bridge arrangement 7
5.2 Position of the eye 8
5.3 View of the sea surface 8
5.4 Horizontal field of vision 8
5.5 Vertical field of vision 9
5.5.1 Vertical field of vision from the conning position above the horizontal plane 9
5.5.2 Vertical field of vision from the conning position below the horizontal plane 9
5.6 Blind sectors 9
5.7 Clear sector 13
5.8 Field of vision from the docking position 13

6 Test procedure 14
6.1 General 14
6.2 Design stage 14
6.3 Harbour acceptance test 15
6.4 Tests for optical properties of the glass 15

Bibliography 16