ISO 11336-1:2023-11 (E)

Large yachts - St rength, weathertightness and watertightness of glazed openings - Part 1: Design criteria, materials, framing and testing of independent glazed openings

Contents

Page

Foreword v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 2

4 Symbols and abbreviated terms 7

5 Design criteria 9
5.1 General 9
5.2 Strength 9
5.3 Watertightness 10
5.4 Weathertightness 10
5.5 Design loads 10
5.5.1 Design pressure for glazed openings in end bulkheads of superstructures and deckhouses on or above the freeboard deck 10
5.5.2 Design pressure for glazed openings and deadlights in the side shell 14
5.6 Scantling determination of panes 15
5.6.1 General 15
5.6.2 Basic pane thickness , t0 , for rectangular or rectangular equivalent glazed openings 16
5.6.3 Basic pane thickness, t0, for circular or circular equivalent glazed openings 16
5.6.4 Design flexural stress of material, A 17
5.6.5 Selection of monolithic pane thickness 17
5.6.6 Selection of laminated pane thickness 18
5.6.7 Type (A) laminates -- Laminates with plies of the same material 18
5.6.8 Insulating glazing unit panes determination 21
5.6.9 Strength requirements of fire-resistant glazing 22
5.6.10 Glazing effective as fall protection 22
5.6.11 Deflection 22

6 Framing 24
6.1 General 24
6.2 Framing types 24
6.3 Framing dimensions 25
6.3.1 General 25
6.3.2 Clear view of >0,45 m2 up to 1 m2 26
6.3.3 Clear view of >1 m2 up to 2,5 m2 26
6.3.4 Clear view >2,5 m2 26
6.4 Support pads 26
6.5 Material requirements for the framing 27

7 Materials 28
7.1 General 28
7.2 Materials selection 28
7.2.1 General 28
7.2.2 Glass 28
7.2.3 Rigid plastic materials 29

7.3 Testing of materials 29
7.3.1 General 29
7.3.2 Glass 29
7.3.3 Rigid plastic materials 30
7.4 Testing of appliances 30
7.4.1 Test procedure for hydrostatic structural testing of marine windows system 30
7.4.2 Motivations 31
7.4.3 Testing plan and expected outcome 31
7.4.4 Apparatus 31
7.4.5 Acceptance criteria 33
7.4.6 Test report 33

8 Storm shutters and deadlights 34
8.1 General 34
8.2 Storm shutters 34
8.2.1 General practice 34
8.2.2 Glazed equivalents to providing storm shutters 34
8.2.3 Construction of storm shutters 35
8.2.4 Design pressures and design flexural stresses 35
8.2.5 Structural model 35
8.2.6 Scantlings 35
8.2.7 Attachment to bulkhead 36
8.3 Robustness of protection of hull openings 36
8.3.1 General practice 36
8.3.2 Equivalent secondary barriers 37
8.3.3 Testing 37
8.3.4 Testing of metal or composite deadlights 37
8.3.5 Testing of equivalent glazing deadlight 37
8.4 Owner's manual 39

Annex A (normative) Unsupported pane dimensions 40

Annex B (normative) Calculation of the stiffness of a pane 42

Annex C (informative) Scantling formula 43

Annex D (informative)StatisticalcoefficientKn and worked example 44

Annex E (informative) Worked examples of equivalent thickness calculationfor Type A laminates .. 45

Annex F (informative) Worked examples of equivalent thickness calculation for Type B laminates . 48

Annex G (informative) Design pressure in lieu of storm shutters 49

Annex H (informative) Changes between ISO 11336-1:2012 and this document 51

Annex I (informative) Direct method for the determination of the glazing laminate cross- section 54

Annex J (informative) Testing of glazing as secondary barriers 58

Bibliography 59