

ISO 11336-1:2023-11 (E)

Large yachts - Strengh, weathertightness and watertightness of glazed openings - Part 1: Design criteria, materials, framing and testing of independent glazed openings

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols and abbreviated terms	7
5	Design criteria	9
5.1	General	9
5.2	Strength	9
5.3	Watertightness	10
5.4	Weathertightness	10
5.5	Design loads	10
5.5.1	Design pressure for glazed openings in end bulkheads of superstructures and deckhouses on or above the freeboard deck	10
5.5.2	Design pressure for glazed openings and deadlights in the side shell	14
5.6	Scantling determination of panes	15
5.6.1	General	15
5.6.2	Basic pane thickness, t_0 , for rectangular or rectangular equivalent glazed openings	16
5.6.3	Basic pane thickness, t_0 , for circular or circular equivalent glazed openings	16
5.6.4	Design flexural stress of material, A	17
5.6.5	Selection of monolithic pane thickness	17
5.6.6	Selection of laminated pane thickness	18
5.6.7	Type (A) laminates -- Laminates with plies of the same material	18
5.6.8	Insulating glazing unit panes determination	21
5.6.9	Strength requirements of fire-resistant glazing	22
5.6.10	Glazing effective as fall protection	22
5.6.11	Deflection	22
6	Framing	24
6.1	General	24
6.2	Framing types	24
6.3	Framing dimensions	25
6.3.1	General	25
6.3.2	Clear view of >0,45 m ² up to 1 m ²	26
6.3.3	Clear view of >1 m ² up to 2,5 m ²	26
6.3.4	Clear view >2,5 m ²	26
6.4	Support pads	26
6.5	Material requirements for the framing	27
7	Materials	28
7.1	General	28
7.2	Materials selection	28
7.2.1	General	28
7.2.2	Glass	28
7.2.3	Rigid plastic materials	29

7.3	Testing of materials	29
7.3.1	General	29
7.3.2	Glass	29
7.3.3	Rigid plastic materials	30
7.4	Testing of appliances	30
7.4.1	Test procedure for hydrostatic structural testing of marine windows system	30
7.4.2	Motivations	31
7.4.3	Testing plan and expected outcome	31
7.4.4	Apparatus	31
7.4.5	Acceptance criteria	33
7.4.6	Test report	33
8	Storm shutters and deadlights	34
8.1	General	34
8.2	Storm shutters	34
8.2.1	General practice	34
8.2.2	Glazed equivalents to providing storm shutters	34
8.2.3	Construction of storm shutters	35
8.2.4	Design pressures and design flexural stresses	35
8.2.5	Structural model	35
8.2.6	Scantlings	35
8.2.7	Attachment to bulkhead	36
8.3	Robustness of protection of hull openings	36
8.3.1	General practice	36
8.3.2	Equivalent secondary barriers	37
8.3.3	Testing	37
8.3.4	Testing of metal or composite deadlights	37
8.3.5	Testing of equivalent glazing deadlight	37
8.4	Owner's manual	39
Annex A (normative) Unsupported pane dimensions		40
Annex B (normative) Calculation of the stiffness of a pane		42
Annex C (informative) Scantling formula		43
Annex D (informative) Statistical coefficient K_n and worked example		44
Annex E (informative) Worked examples of equivalent thickness calculation for Type A laminates ..		45
Annex F (informative) Worked examples of equivalent thickness calculation for Type B laminates .		48
Annex G (informative) Design pressure in lieu of storm shutters		49
Annex H (informative) Changes between ISO 11336-1:2012 and this document		51
Annex I (informative) Direct method for the determination of the glazing laminate cross- section		54
Annex J (informative) Testing of glazing as secondary barriers		58
Bibliography		59