

ISO/TR 9814:2025-06 (E)

Ships and marine technology - Good practices of preventing capsizing during turning of ships with large profile height

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Abbreviated terms	2
5	Analysis of capsized accidents of five ships	3
5.1	General	3
5.2	Ship categories based on cargo space requirements	4
5.2.1	Weight carrier	4
5.2.2	Volume carrier	4
5.2.3	Area carrier	4
5.3	Analysis of capsized accidents	4
5.3.1	General	4
5.3.2	Similarities	4
5.3.3	Differences	5
6	Effect of KG on the GZ curve	5
6.1	KG and its role in capsizing accidents	5
6.2	Characteristics of hull form and GZ curves	9
6.2.1	General	9
6.2.2	Hull forms with two inflection points along the GZ curve	9
7	Three good practices to prevent capsizing during turning of ships	10
7.1	General	10
7.2	Semi-automatic inclining tests before loaded departure	10
7.2.1	General	10
7.2.2	Features of inclining test before departure	11
7.2.3	Stability screening without inclining test	12
7.3	Maximum heeling angle while turning	14
7.3.1	General	14
7.3.2	Maritime autonomous surface ships	15
7.3.3	Considerations on cargo slippage	16
7.4	Precise calculation of free surface moment (FSM)	17
7.4.1	Slack limit of NAPA software	17
7.4.2	FSM at 98 % filling level	17
7.4.3	Improvement of stability calculation software	18
	Annex A (informative) Cases of capsizing accidents	19
	Annex B (informative) Additional information on ship features	28
	Bibliography	30