

ISO 6185-3:2001-11 (E)

Inflatable boats - Part 3: Boats with a maximum motor power rating of 15 kW and greater

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | v |
| Introduction | | vi |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Materials | 3 |
| 4.1 | General | 3 |
| 4.2 | Reinforced materials making up the hull (excluding glass-fibre-reinforced plastics components) | 3 |
| 4.2.1 | Requirements | 3 |
| 4.2.2 | Test methods | 4 |
| 4.3 | Wood | 5 |
| 4.3.1 | General | 5 |
| 4.3.2 | Plywood | 5 |
| 4.3.3 | Constructional timbers | 6 |
| 4.4 | Metal and synthetic material parts | 6 |
| 4.5 | Glass-fibre-reinforced plastics | 6 |
| 5 | Functional components | 6 |
| 5.1 | Conditioning | 6 |
| 5.2 | Hull fittings | 6 |
| 5.2.1 | Requirement | 6 |
| 5.2.2 | Test method | 6 |
| 5.3 | Manual lifting and carrying devices | 6 |
| 5.3.1 | Requirement | 6 |
| 5.3.2 | Test method | 6 |
| 5.4 | Valves | 7 |
| 5.4.1 | Inflation | 7 |
| 5.4.2 | Deflation | 7 |
| 5.5 | Rowlocks and oars | 7 |
| 5.5.1 | Requirements | 7 |
| 5.5.2 | Abrasion damage | 7 |
| 5.5.3 | Prevention from loosening | 7 |
| 5.5.4 | Strength of rowlocks | 8 |
| 5.5.5 | Use of the rowlocks and oars | 8 |
| 5.6 | Transom (where applicable) | 8 |
| 5.6.1 | Requirement | 8 |
| 5.6.2 | Test method | 8 |
| 5.7 | Hull drainage | 8 |
| 5.8 | Remote steering system (where offered as standard or optional equipment) | 8 |
| 5.9 | Motor-securing line attachment (outboard engines only) | 9 |
| 5.10 | Towing device (all types) | 9 |
| 5.11 | Seating and attachment systems (where offered as a standard or optional equipment) | 9 |
| 5.12 | Electrical installations (where offered as standard or optional equipment)) | 9 |
| 5.13 | Fuel systems (where applicable) | 9 |
| 5.14 | Ventilation of petrol motor and petrol tank compartments (where applicable) | 9 |

| | | |
|---|--|----|
| 6 | Safety requirements of the completed boat | 9 |
| 6.1 | Maximum permissible number of persons | 9 |
| 6.2 | Maximum motor power | 10 |
| 6.3 | Static stability of the boat | 10 |
| 6.3.1 | Requirement | 10 |
| 6.3.2 | Test method | 10 |
| 6.3.3 | Stability factor (Type VIII boats only) | 11 |
| 6.4 | Maximum load capacity | 11 |
| 6.4.1 | Requirement | 11 |
| 6.4.2 | Test method | 12 |
| 6.5 | Design working pressures | 12 |
| 6.6 | Strength of the hull | 12 |
| 6.6.1 | Requirement | 12 |
| 6.6.2 | Test method | 12 |
| 6.7 | Safety ropes and grab handles | 13 |
| 6.7.1 | Requirement | 13 |
| 6.7.2 | Test method | 13 |
| 6.8 | Residual buoyancy | 13 |
| 6.8.1 | Requirement | 13 |
| 6.8.2 | Test method | 13 |
| 6.9 | Manoeuvrability | 13 |
| 6.9.1 | Requirement | 13 |
| 6.9.2 | Test method | 13 |
| 6.10 | Compartmentation | 13 |
| 6.11 | Field of vision from the helm position | 14 |
| 6.12 | Provision for (a) liferaft(s) (Type VIII boats only) | 14 |
| 7 | Performance test | 14 |
| 7.1 | General | 14 |
| 7.2 | Drop test (RIBs only) | 15 |
| 7.2.1 | Requirement | 15 |
| 7.2.2 | Test method | 15 |
| 7.3 | In-water performance | 15 |
| 7.3.1 | Requirement | 15 |
| 7.3.2 | Test methods | 16 |
| 7.4 | Strength of the towing device | 16 |
| 7.4.1 | Requirement | 16 |
| 7.4.2 | Test method | 16 |
| 7.5 | Rowing test (where applicable, see 5.5) | 17 |
| 7.6 | Watertightness test (not applicable to open floor, self-bailing craft) | 17 |
| 7.6.1 | Requirement | 17 |
| 7.6.2 | Test method | 18 |
| 7.7 | Manoeuvring-speed test | 18 |
| 7.8 | Bailing test (Type VIII boats only) | 18 |
| 7.8.1 | Requirement | 18 |
| 7.8.2 | Test method | 18 |
| 8 | Builder's plate(s) | 18 |
| 9 | Operator's instructions and warning notes | 19 |
| 10 | Standard equipment | 20 |
| Annex A (informative) General arrangement of a typical type VII boat | | 21 |
| Annex B (informative) General arrangement of a typical Type VIII boat | | 22 |
| Bibliography | | 23 |