

ISO 12217-2:2002-04 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 2: Sailing boats of hull length greater than or equal to 6 m

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
3.1	Primary	2
3.2	Hazards	3
3.3	Downflooding	3
3.4	Dimensions, areas and angles	4
3.5	Condition, mass and volume	5
3.6	Other terms and definitions	7
4	Symbols	9
5	Procedure	10
5.1	Maximum total load	10
5.2	Sailing or non-sailing	10
5.3	Tests, calculations and requirements to be applied	10
6	Requirements for monohull boats	10
6.1	Requirements to be applied	10
6.2	Downflooding	12
6.3	Angle of vanishing stability and minimum mass	14
6.4	Stability index (STIX)	16
6.5	Knockdown-recovery test	19
6.6	Wind stiffness test	20
6.7	Flotation requirements	22
6.8	Capsize-recovery test	22
7	Requirements for catamarans and trimarans	23
7.1	Requirements to be applied	23
7.2	Downflooding openings	23
7.3	Downflooding height	23
7.4	Stability information	24
7.5	Warning symbols	24
7.6	Buoyancy when inverted	24
7.7	Breaking waves	25
8	Application	25
8.1	Deciding the design category	25
8.2	Meaning of the design categories (see Table 8)	25
Annex A (normative)	Full method for required downflooding height	27
Annex B (normative)	Methods for calculating downflooding angle	29
Annex C (normative)	Determining properties of the curve of righting levers	31

Annex D (normative) Method for calculating reserve of buoyancy after inversion or flooding	33
Annex E (normative) Flotation material and elements	35
Annex F (normative) Information for owner's manual	37
Annex G (informative) Determining wind heeling information	40
Annex H (informative) Summary of requirements	42
Annex I (informative) Worksheets	45
Bibliography	59