ISO 12217-2:2002-04 (E)

Small craft - Stability and buoyancy assessment and categorization - Part 2: Sailing boats of hull length greater than or equal to 6 m

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms and definitions 2
3.1 Primary 2
3.2 Hazards 3
3.3 Downflooding 3
3.4 Dimensions, areas and angles 4
3.5 Condition, mass and volume 5
3.6 Other terms and definitions 7

4 Symbols 9

5 Procedure 10
5.1 Maximum total load 10
5.2 Sailing or non-sailing 10
5.3 Tests, calculations and requirements to be applied 10

6 Requirements for monohull boats 10
6.1 Requirements to be applied 10
6.2 Downflooding 12
6.3 Angle of vanishing stability and minimum mass 14
6.4 Stability index (STIX) 16
6.5 Knockdown-recovery test 19
6.6 Wind stiffness test 20
6.7 Flotation requirements 22
6.8 Capsize-recovery test 22

7 Requirements for catamarans and trimarans 23
7.1 Requirements to be applied 23
7.2 Downflooding openings 23
7.3 Downflooding height 23
7.4 Stability information 24
7.5 Warning symbols 24
7.6 Buoyancy when inverted 24
7.7 Breaking waves 25

8 Application 25
8.1 Deciding the design category 25
8.2 Meaning of the design categories (see Table 8) 25

Annex A (normative) Full method for required downflooding height 27

Annex B (normative) Methods for calculating downflooding angle 29

Annex C (normative) Determining properties of the curve of righting levers 31

Annex D (normative) Method for calculating reserve of buoyancy after inversion or flooding 33

Annex E (normative) Flotation material and elements 35

Annex F (normative) Information for owner's manual 37

Annex G (informative) Determining wind heeling information 40

Annex H (informative) Summary of requirements 42

Annex I (informative) Worksheets 45

Bibliography 59