

ISO/TS 21139-21:2019 (E)

Permanence and durability of commercial prints — Part 21: In-window display — Light and ozone stability

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Use profile
4.1	General
4.2	Environmental light condition
4.3	Environmental ozone condition
5	Test method
5.1	General
5.2	Sample preparation
5.2.1	Outline
5.2.2	Test target
5.2.3	Storage conditions between printing and light or ozone exposure test
5.2.4	Reference samples
5.2.5	Backing of the specimens
5.3	Light exposure
5.3.1	Outline
5.3.2	Spectral power distribution
5.3.3	Light intensity
5.3.4	Temperature and humidity
5.3.5	Duration of the light exposures
5.4	Ozone test
5.4.1	Outline
5.4.2	Apparatus
5.4.3	Test procedure
5.4.4	Test conditions
5.4.4.1	General
5.4.4.2	Ozone concentration
5.4.4.3	Temperature and humidity
5.4.4.4	Duration of the ozone exposures
6	Measurement
6.1	General
6.2	Measurement conditions
6.3	Calculation of colour difference
7	Data analysis
7.1	General
7.2	Image quality parameter for data analysis
7.3	Environmental conditions
7.4	Estimation of time to reach certain change
8	Reporting
Annex A	(informative) Display window type and lighting design

- A.1 Type of display windows**
- A.2 Lighting design**
- A.3 Air conditioning (ozone, temperature and humidity control)**

Annex B (informative) Example of test results

- B.1 Outline**
- B.2 Light exposure test**
 - B.2.1 Samples**
 - B.2.2 Test procedures**
 - B.2.3 Test results**
- B.3 Evaluation**
 - B.3.1 Image quality parameter**
 - B.3.2 Visual assessment**
 - B.3.3 Correspondence of measurements to the visual assessments**
 - B.3.4 Estimation of the time to reach certain change**

Page count: 14