

# DIN 15765:2020-11 (E)

## Entertainment Technology - Multi-core cable systems for mobile productions and entertainment technology

---

<b>Contents</b>	<b>Page</b>
Foreword .....	4
Introduction .....	5
1 Scope .....	6
2 Normative references .....	6
3 Terms and definitions.....	7
4 Types .....	8
4.1 General .....	8
4.2 Power class.....	8
4.3 Number of circuits .....	8
4.4 Connectors and contact assignment.....	9
4.4.1 General .....	9
4.4.2 Types and contact assignment for different connectors .....	9
5 Requirements for connectors.....	11
5.1 General requirements .....	11
5.2 Particular requirements .....	12
6 Requirements for plugboxes .....	12
7 Cables .....	12
7.1 General .....	12
7.2 Requirements for the insulating material.....	13
7.3 Conductor cross-section.....	13
7.4 Cable length.....	13
8 Electrical safety.....	13
8.1 General .....	13
8.2 Personal protection.....	14
8.3 Cable protection .....	14
Annex A (normative) Criteria for the dimensional accuracy of type D .....	15
Annex B (informative) Permitted cable lengths for PVC or rubber cables .....	16
Annex C (informative) Criteria for the configurations of connectors.....	17
C.1 Configurations of connectors in multi-core cable systems.....	17
C.1.1 General .....	17
C.1.2 Configuration 1 .....	17
C.1.3 Configuration 2 .....	18
Bibliography.....	20
<b>Figures</b>	
Figure A.1 — Types and dimensions.....	15
Figure C.1 — Multi-core cable system, configuration 1 .....	17
Figure C.2 — Multi-core cable system, configuration 2 A .....	18
Figure C.3 — Multi-core cable system, configuration 2 B .....	19

## Tables

<b>Table 1 — Power classes.....</b>	<b>8</b>
<b>Table 2 — Number of circuits.....</b>	<b>8</b>
<b>Table 3 — Types and contact assignment for the different connectors .....</b>	<b>9</b>
<b>Table 4 — Minimum cross-sections .....</b>	<b>13</b>
<b>Table B.1 — Permitted threshold lengths in the TN system; 400/230 V 50 Hz (excerpt from DIN VDE 0100 Supplement 5:2017-10, Table A21).....</b>	<b>16</b>
<b>Table B.2 — Permitted threshold lengths in the TN system; 400/230 V 50 Hz (excerpt from DIN VDE 0100 Supplement 5:2017-10, Table A22).....</b>	<b>16</b>