ISO/TR 17321-5:2021 (E)

Graphic technology and photography — Colour characterization of digital still cameras (DSCs) — Part 5: Colour targets including saturated colours for colour characteristic evaluation test for colorimetric image capture

Contents

COI	itoi	
		Foreword
		Introduction
1		Scope
2		Normative references
3		Terms and definitions
4		Highly-saturated colour targets
	4.1 4.2 4.2.3 4.2.3 4.2.3 4.2.3 4.3.3 4.3.3 4.3.3	Selection of spectra database Spectral reconstruction from the eigenvectors General Boundary colour generation Saturated-colour generation using the reference spectra distribution set Artificial (LED-based) spectra whose wavelength peak is on colour-difference-sensitive wavelength (CDSW) General The method to define the colour-difference-sensitive wavelength (CDSW)
5		FOM metric for evaluation of overall sensor spectral sensitivities, used in the digital cameras
	5.1 5.2 5.3 5.4 5.5	General Evaluation metrics for OSSS Advantages and disadvantages of ΔE (deltaE) evaluation How 17321-5 datasets can be used for FOMs Worked examples
Annex	κA	(informative) Selection and eigenvectors of spectral distribution set
	A.1 A.2	Selection of spectral distribution set Eigenvectors of selected spectral distribution set
Annex	κВ	(informative) Colour gamut of boundary colour
Annex	(C	(informative) Worked example for spectral distribution generation of Pointer's surface colours
	C.1 C.2 C.3 C.4	General Calculation of objective colour chroma and C c * C r * ratio Calculation of maximum C c * C r * ratio Generation of spectral distribution candidates
Annex	(D	(informative) Background information for defining CDSW
Annex	κE	(informative) Additional 410nm to colour-difference-sensitive wavelengths (CDSW)
Annex	ς F	(informative) Colour differences of patches of CDSW target
Annex	c G	(informative) Spectral distribution of CDSW target for ITU-R BT.2020
Annex	κH	(informative) Spectral distribution dataset for users to download