

# ISO/TS 21139-22:2023-05 (E)

## Permanence and durability of commercial prints - Part 22: Backlit display in indoor or shaded outdoor conditions - Light stability

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.1</b>	<b>Measures of exposure severity .....</b>	<b>2</b>
<b>3.2</b>	<b>Exposure conditions .....</b>	<b>2</b>
<b>3.3</b>	<b>Abbreviations .....</b>	<b>3</b>
<b>4</b>	<b>Use profile .....</b>	<b>4</b>
<b>4.1</b>	<b>General .....</b>	<b>4</b>
<b>4.2</b>	<b>Parameters of backlit display .....</b>	<b>4</b>
<b>4.3</b>	<b>Frontside exposure and environmental conditions .....</b>	<b>6</b>
<b>4.4</b>	<b>Equivalent test conditions .....</b>	<b>6</b>
<b>4.4.1</b>	<b>Severity weighted exposure condition .....</b>	<b>6</b>
<b>4.4.2</b>	<b>Equivalent test duration .....</b>	<b>8</b>
<b>4.5</b>	<b>Relevance of use .....</b>	<b>9</b>
<b>5</b>	<b>Test methods .....</b>	<b>10</b>
<b>5.1</b>	<b>General .....</b>	<b>10</b>
<b>5.2</b>	<b>Sample preparation .....</b>	<b>10</b>
<b>5.2.1</b>	<b>Outline .....</b>	<b>10</b>
<b>5.2.2</b>	<b>Test target .....</b>	<b>10</b>
<b>5.2.3</b>	<b>Sample labelling and marking .....</b>	<b>10</b>
<b>5.2.4</b>	<b>Storage conditions between printing and light exposure test .....</b>	<b>11</b>
<b>5.2.5</b>	<b>Reference samples .....</b>	<b>11</b>
<b>5.2.6</b>	<b>Backing of the specimens .....</b>	<b>11</b>
<b>5.3</b>	<b>Light exposure .....</b>	<b>11</b>
<b>5.3.1</b>	<b>Test method and filter condition .....</b>	<b>11</b>
<b>5.3.2</b>	<b>Light intensity .....</b>	<b>11</b>
<b>5.3.3</b>	<b>Temperature and humidity .....</b>	<b>11</b>
<b>5.3.4</b>	<b>Duration of the light exposure .....</b>	<b>12</b>
<b>5.4</b>	<b>Exposure of the frontside of the print .....</b>	<b>12</b>
<b>5.4.1</b>	<b>Specimen mounting for frontside exposure .....</b>	<b>12</b>
<b>5.4.2</b>	<b>Duration of the frontside exposure .....</b>	<b>12</b>
<b>5.5</b>	<b>Exposure of the backside of the print .....</b>	<b>12</b>
<b>5.5.1</b>	<b>Specimen mounting for backside exposure .....</b>	<b>12</b>
<b>5.5.2</b>	<b>Duration of the backside exposure .....</b>	<b>12</b>
<b>6</b>	<b>Measurement .....</b>	<b>12</b>
<b>6.1</b>	<b>General .....</b>	<b>12</b>
<b>6.2</b>	<b>Measurement conditions .....</b>	<b>13</b>
<b>7</b>	<b>Data analysis .....</b>	<b>14</b>
<b>7.1</b>	<b>General .....</b>	<b>14</b>
<b>7.2</b>	<b>Image quality parameter for data analysis .....</b>	<b>14</b>
<b>7.3</b>	<b>Equivalent test conditions .....</b>	<b>14</b>

7.4	Estimation of time to reach certain change .....	14
8	Test report .....	15
	Annex A (normative) Relative severity of the relative spectral irradiance .....	17
	Annex B (normative) Characterization of an example LED light box .....	21
	Annex C (informative) sRGB test target .....	25
	Annex D (informative) Overview of test conditions in backlit context .....	26
	Bibliography .....	27