

ISO 3664:2025-07 (E)

Graphic technology and photography - Viewing conditions

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Viewing condition requirements	5
4.1	General requirements	5
4.1.1	Applicability	5
4.1.2	Ambient conditions	5
4.1.3	Viewing apparatus	6
4.1.4	Spectral conditions for the reference illuminant	6
4.1.5	Maintenance	7
4.2	Conditions for critical comparison (ISO viewing conditions P1, P3, T1)	7
4.2.1	Applicability	7
4.2.2	Illumination	7
4.2.3	Illuminance (P1 and P3)	8
4.2.4	Surround and backing for reflection viewing (P1 and P3)	8
4.2.5	Luminance at the surface of the transparency illuminator (T1)	9
4.2.6	Transparency illuminator diffusion characteristics (T1)	9
4.2.7	Transparency surround (T1)	9
4.2.8	Relationship between transparency luminance and print illuminance (P1 or P3 and T1)	9
4.3	Conditions for practical appraisal of prints (including routine inspection) (ISO viewing condition P2 and P4)	10
4.3.1	Applicability	10
4.3.2	Illumination	10
4.3.3	Illuminance	10
4.3.4	Surround and backing	10
4.4	Conditions for viewing small transparencies by projection (ISO viewing conditions T2) ...	11
4.4.1	Applicability	11
4.4.2	Illumination	11
4.4.3	Luminance	11
4.4.4	Uniformity of the projection screen luminance	11
4.4.5	Surround	11
4.4.6	Ambient light and veiling flare	11
4.4.7	Resolution	11
4.4.8	Distortion	11
5	Test methods	12
5.1	Spectral measurements	12
5.2	Illuminance and luminance	12
5.3	Resolution assessment for projection viewing apparatus	12
Annex A (informative) Summary of viewing conditions specified in this document		13
Annex B (informative) Validity of requirements for reference viewing conditions for a print		15
Annex C (informative) Guidelines for judging and exhibiting photographs		18
Annex D (normative) Conformance test to UV content contained in illumination for P3 and P4 condition		20
Annex E (informative) Considerations for simultaneous comparison of samples between multiple reference viewing environments		24
Bibliography		28