

ISO/TR 17243-1:2014-12 (E)

Machine tool spindles - Evaluation of machine tool spindle vibrations by measurements on spindle housing - Part 1: Spindles with rolling element bearings and integral drives operating at speeds between 600 min⁻¹ and 30000 min⁻¹

Contents

	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Preliminary operations	3
4.1 General	3
4.2 Process load	3
4.3 Spindle speed	3
4.4 Thermal conditions	4
4.5 Spindle position and orientation	4
4.6 Tool or workpiece balancing	4
4.7 Spindle chuck	4
4.8 Spindle cooling	5
4.9 Drawbar	5
4.10 Background vibration	5
4.11 Idle operation	5
5 Measurement and operational procedures	5
5.1 Measuring instruments	5
5.2 Measurement locations/directions	6
5.3 Sensor mounting procedures	7
6 Evaluation parameters	8
6.1 Vibration velocity parameter	8
6.2 Vibration acceleration parameter	9
6.3 Demodulated vibration spectra bearing analysis methods	10
7 Spindle classification	10
7.1 General	10
7.2 Classification according to rated power	10
7.3 Classification according to maximum spindle speed	10
7.4 Classification according to bearing type	10
8 Evaluation	11
8.1 General	11
8.2 Criterion I: vibration magnitude	11
8.3 Criterion II: change in vibration magnitude	12
8.4 General zone boundaries	12
8.5 Examples of evaluation zone boundary values	13
8.6 Operational limits	14
Annex A (informative) Introduction to alternative bearing condition assessment techniques	16
Bibliography	18

Bibliography	18
--------------------	----