

# ISO 3408-4:2006-06 (E)

## Ball screws - Part 4: Static axial rigidity

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols and subscripts .....</b>	<b>1</b>
<b>4.1</b>	<b>Symbols .....</b>	<b>1</b>
<b>4.2</b>	<b>Subscripts .....</b>	<b>2</b>
<b>5</b>	<b>Determination of static axial rigidity, R .....</b>	<b>3</b>
<b>5.1</b>	<b>General .....</b>	<b>3</b>
<b>5.2</b>	<b>Static axial rigidity, R .....</b>	<b>5</b>
<b>5.3</b>	<b>Static axial rigidity of ball screw, R<sub>bs</sub> .....</b>	<b>5</b>
<b>5.4</b>	<b>Static axial rigidity of ball screw shaft, R<sub>s</sub> .....</b>	<b>5</b>
<b>5.4.1</b>	<b>General .....</b>	<b>5</b>
<b>5.4.2</b>	<b>Rigid mounting of ball screw shaft at one end .....</b>	<b>5</b>
<b>5.4.3</b>	<b>Rigid mounting of ball screw shaft at both ends .....</b>	<b>6</b>
<b>5.5</b>	<b>Static axial rigidity of ball nut unit, R<sub>nu</sub> .....</b>	<b>6</b>
<b>5.5.1</b>	<b>Static axial rigidity of ball nut unit with backlash, R<sub>nu1</sub> .....</b>	<b>6</b>
<b>5.5.2</b>	<b>Static axial rigidity of symmetrically preloaded ball nut unit, R<sub>nu2,4</sub> .....</b>	<b>10</b>
<b>5.5.3</b>	<b>Correction for accuracy, f<sub>ar</sub> .....</b>	<b>12</b>
<b>Annex A (informative)</b>	<b>Example calculation of static axial rigidity in preloaded symmetrical double nut system .....</b>	<b>14</b>
<b>Annex B (informative)</b>	<b>Correction for load application, f<sub>al</sub> .....</b>	<b>17</b>