ISO 3408-5:2006-06 (E)

Ball screws - Part 5: Static and dynamic axial load ratings and operational life

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Terms and definitions 1

4 Symbols and subscripts 2
4.1 Symbols 2
4.2 Subscripts 3

5 Basic axial load ratings 4
5.1 Basic static axial load rating, C0a 4
5.2 Basic dynamic axial load rating, Ca 4

6 Modified axial load ratings 5
6.1 Modified static axial load rating, C0am 5
6.1.1 General equation 5
6.1.2 Correction for surface hardness, fh0 5
6.1.3 Correction for accuracy, fac 6
6.2 Modified dynamic axial load rating, Cam 6
6.2.1 General equation 6
6.2.2 Correction for surface hardness, fh 6
6.2.3 Correction for accuracy, fac 6
6.2.4 Influence of material melting process, fm 6

7 Life 7
7.1 Equivalent rotational speed and equivalent axial load 7
7.1.1 General 7
7.1.2 Ball screw with backlash between ball nut and screw shaft 7
7.1.3 Ball screw with preloaded ball nuts on screw shaft 10
7.2 Nominal life, L or Lh 12
7.2.1 Ball screw with backlash between ball nut and screw shaft 12
7.2.2 Ball screw with preloaded ball nuts on screw shaft 13
7.2.3 Resulting life, Lr 13
7.2.4 Nominal life, Lar or Lhar, with reliability factor, far (see Table 3) 13
7.3 Modified life, Lm or Lhm 14
7.3.1 Ball screw with backlash between ball nut and screw shaft 14
7.3.2 Ball screw with preloaded ball nuts on screw shaft 14
7.3.3 Modified resulting life, Lmr 14
7.3.4 Modified life, Lmar or Lhmar, with reliability factor, far (see Table 3) 14