ISO/ASTM 52911-2:2019-09 (E)

Additive manufacturing - Design - Part 2: Laser-based powder bed fusion of polymers

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Symbols and abbreviated terms 2
4.1 Symbols 2
4.2 Abbreviated terms 3

5 Characteristics of powder bed fusion (PBF) processes 3
5.1 General 3
5.2 Size of the parts 3
5.3 Benefits to be considered in regard to the PBF process 4
5.4 Limitations to be considered in regard to the PBF process 4
5.5 Economic and time efficiency 5
5.6 Feature constraints (islands, overhang, stair-step effect) 5
5.6.1 General 5
5.6.2 Islands 5
5.6.3 Overhang 6
5.6.4 Stair-step effect 6
5.7 Dimensional, form and positional accuracy 6
5.8 Data quality, resolution, representation 6

6 Design guidelines for laser-based powder bed fusion of polymers (LB-PBF/P) 7
6.1 General 7
6.2 Material and structural characteristics 7
6.3 Anisotropy of the material characteristics 8
6.4 Build orientation, positioning and arrangement 9
6.4.1 General 9
6.4.2 Powder coating 9
6.4.3 Part location in the build chamber 9
6.4.4 Oversintering 9
6.4.5 Packing parts efficiently in the build chamber 9
6.5 Surface roughness 10
6.6 Post-production finishing 10
6.7 Design considerations 11
6.7.1 Allowing for powder removal 11
6.7.2 Reducing warpage 11
6.7.3 Wall thickness 11
6.7.4 Gaps, cylinders and holes 11
6.7.5 Lattice structures 12
6.7.6 Fluid channels 12
6.7.7 Springs and elastic elements 13
6.7.8 Connecting elements and fasteners 13
6.7.9 Static assemblies 14
6.7.10 Movable assemblies 15

6.7.11 Bearings 15
6.7.12 Joints 15
6.7.13 Integrated markings 16
6.7.14 Cutting and joining 16
6.8 Example applications 17
6.8.1 Functional toy car with integrated spring 17
6.8.2 Robot gripper 18

7 General design consideration 19

Bibliography 20