

DIN EN ISO/ASTM 52911-2:2020-06 (E)

Additive manufacturing - Design - Part 2: Laser-based powder bed fusion of polymers (ISO/ASTM 52911-2:2019)

Contents	Page
European foreword	4
Foreword	5
Introduction	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Symbols and abbreviated terms	8
4.1 Symbols	8
4.2 Abbreviated terms	9
5 Characteristics of powder bed fusion (PBF) processes	9
5.1 General	9
5.2 Size of the parts	9
5.3 Benefits to be considered in regard to the PBF process	10
5.4 Limitations to be considered in regard to the PBF process	10
5.5 Economic and time efficiency	11
5.6 Feature constraints (islands, overhang, stair-step effect)	11
5.6.1 General	11
5.6.2 Islands	11
5.6.3 Overhang	12
5.6.4 Stair-step effect	12
5.7 Dimensional, form and positional accuracy	12
5.8 Data quality, resolution, representation	12
6 Design guidelines for laser-based powder bed fusion of polymers (LB-PBF/P)	13
6.1 General	13
6.2 Material and structural characteristics	13
6.3 Anisotropy of the material characteristics	14
6.4 Build orientation, positioning and arrangement	15
6.4.1 General	15
6.4.2 Powder coating	15
6.4.3 Part location in the build chamber	15
6.4.4 Oversintering	15
6.4.5 Packing parts efficiently in the build chamber	15
6.5 Surface roughness	16
6.6 Post-production finishing	16
6.7 Design considerations	17
6.7.1 Allowing for powder removal	17
6.7.2 Reducing warpage	17
6.7.3 Wall thickness	17
6.7.4 Gaps, cylinders and holes	17
6.7.5 Lattice structures	18
6.7.6 Fluid channels	18
6.7.7 Springs and elastic elements	19
6.7.8 Connecting elements and fasteners	19
6.7.9 Static assemblies	20
6.7.10 Movable assemblies	21

6.7.11	Bearings.....	21
6.7.12	Joints.....	21
6.7.13	Integrated markings	22
6.7.14	Cutting and joining.....	22
6.8	Example applications	23
6.8.1	Functional toy car with integrated spring	23
6.8.2	Robot gripper.....	24
7	General design consideration.....	25
Bibliography.....		26