

# DIN EN ISO/ASTM 52911-2:2020-06 (E)

## Additive manufacturing - Design - Part 2: Laser-based powder bed fusion of polymers ( ISO/ASTM 52911-2:2019)

---

| <b>Contents</b>   | <b>Page</b> |
|---|-------------|
| European foreword .....   | 4           |
| Foreword .....  | 5           |
| Introduction .....  | 6           |
| <b>1 Scope</b> .....  | <b>7</b>    |
| <b>2 Normative references</b> .....   | <b>7</b>    |
| <b>3 Terms and definitions</b> .....  | <b>7</b>    |
| <b>4 Symbols and abbreviated terms</b> .....  | <b>8</b>    |
| 4.1 Symbols .....   | 8           |
| 4.2 Abbreviated terms .....   | 9           |
| <b>5 Characteristics of powder bed fusion (PBF) processes</b> .....                       | <b>9</b>    |
| 5.1 General .....   | 9           |
| 5.2 Size of the parts .....   | 9           |
| 5.3 Benefits to be considered in regard to the PBF process .....                          | 10          |
| 5.4 Limitations to be considered in regard to the PBF process .....                       | 10          |
| 5.5 Economic and time efficiency .....  | 11          |
| 5.6 Feature constraints (islands, overhang, stair-step effect) .....                      | 11          |
| 5.6.1 General .....   | 11          |
| 5.6.2 Islands .....   | 11          |
| 5.6.3 Overhang .....  | 12          |
| 5.6.4 Stair-step effect .....   | 12          |
| 5.7 Dimensional, form and positional accuracy .....                                       | 12          |
| 5.8 Data quality, resolution, representation .....  | 12          |
| <b>6 Design guidelines for laser-based powder bed fusion of polymers (LB-PBF/P)</b> ..... | <b>13</b>   |
| 6.1 General .....   | 13          |
| 6.2 Material and structural characteristics .....   | 13          |
| 6.3 Anisotropy of the material characteristics .....                                      | 14          |
| 6.4 Build orientation, positioning and arrangement .....                                  | 15          |
| 6.4.1 General .....   | 15          |
| 6.4.2 Powder coating .....  | 15          |
| 6.4.3 Part location in the build chamber .....  | 15          |
| 6.4.4 Oversintering .....   | 15          |
| 6.4.5 Packing parts efficiently in the build chamber .....                                | 15          |
| 6.5 Surface roughness .....   | 16          |
| 6.6 Post-production finishing .....   | 16          |
| 6.7 Design considerations .....   | 17          |
| 6.7.1 Allowing for powder removal .....   | 17          |
| 6.7.2 Reducing warpage .....  | 17          |
| 6.7.3 Wall thickness .....  | 17          |
| 6.7.4 Gaps, cylinders and holes .....   | 17          |
| 6.7.5 Lattice structures .....  | 18          |
| 6.7.6 Fluid channels .....  | 18          |
| 6.7.7 Springs and elastic elements .....  | 19          |
| 6.7.8 Connecting elements and fasteners .....   | 19          |
| 6.7.9 Static assemblies .....   | 20          |
| 6.7.10 Movable assemblies .....   | 21          |

|          |   |           |
|----------|---|-----------|
| 6.7.11   | Bearings.....                                   | 21        |
| 6.7.12   | Joints.....                                     | 21        |
| 6.7.13   | Integrated markings .....                       | 22        |
| 6.7.14   | Cutting and joining.....                        | 22        |
| 6.8      | Example applications .....                      | 23        |
| 6.8.1    | Functional toy car with integrated spring ..... | 23        |
| 6.8.2    | Robot gripper.....                              | 24        |
| <b>7</b> | <b>General design consideration .....</b>       | <b>25</b> |
|          | <b>Bibliography.....</b>                        | <b>26</b> |