ISO 16573-2:2022-02 (E)

Steel - Measurement method for the evaluation of hydrogen embrittlement resistance of high-strength steels - Part 2: Slow strain rate test

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**

4 Principle ... **1**

5 Specimen preparation ... **2**
5.1 General ... 2
5.2 Cylindrical type specimen ... 2
5.3 Flat type specimen ... 3

6 Hydrogen charging methods ... **4**
6.1 General ... 4
6.2 Cathodic charging ... 4
6.2.1 Hydrogen charging solution ... 4
6.2.2 Hydrogen charging conditions ... 4
6.3 Hydrogen absorption in aqueous solution at free corrosion potential ... 5
6.4 Hydrogen absorption in atmospheric corrosion environments ... 5
6.5 Hydrogen absorption in high pressure hydrogen gas ... 5

7 Preparation of electroplating solution and electroplating condition ... **5**
7.1 General ... 5
7.2 Electroplating solution ... 5
7.3 Electroplating conditions ... 6

8 Slow strain rate test ... **6**
8.1 General ... 6
8.2 Procedure ... 6
8.3 Presentation of the results ... 7

9 Post-test specimen treatment ... **9**

10 Hydrogen thermal desorption ... **10**
10.1 General ... 10
10.2 Experimental apparatus (gas chromatograph) ... 10
10.3 Experimental apparatus (mass spectrometry) ... 11

11 Test report ... **11**

Bibliography ... **12**