

ISO/ASTM TR 52906:2022-05 (E)

Additive manufacturing - Non-destructive testing - Intentionally seeding flaws in metallic parts

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Abbreviated terms	2
5	Typical AM flaws	3
6	Procedure to produce replicas	7
7	Seeding approaches	7
7.1	General	7
7.2	CAD seeding	8
7.3	AM process manipulation replicas	10
7.3.1	General	10
7.3.2	Entrapped unsintered powder	11
7.3.3	Manual insertion of high-density inclusions	11
7.4	Post-production mechanical introduction of replicas	11
7.5	Significance and use for homogeneity	12
8	AM process manipulation for L-PBF and L-DED	14
8.1	General	14
8.2	AM machine parameter manipulation	14
8.3	Applicable flaw-seeding approaches as a function of desired flaw type	15
8.3.1	General	15
8.3.2	Porosity or voids (increased power density)	15
8.3.3	Surface-connected flaws	15
8.4	Applicable flaw-seeding approach as a function of AM process	16
8.5	Applicable flaw-seeding approach as a function of AM material	17
8.5.1	General	17
8.5.2	High-density inclusions	18
9	Applicable flaw-seeding approach as a function of post processing machining	18
9.1	General	18
9.2	Mechanical machining	18
9.3	Electrode discharge machining replicas	18
9.4	Laser drilling replicas	18
Bibliography		20