

DIN EN 13492:2018-07 (E)

Geosynthetic barriers - Characteristics required for use in the construction of liquid waste disposal sites, transfer stations or secondary containment

Contents		Page
European foreword		5
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms, definitions and abbreviations	10
3.1	Terms and definitions	10
3.2	Abbreviations	12
4	Characteristics and corresponding methods of test	13
4.1	General	13
4.2	Types of applications	13
4.2.1	General	13
4.2.2	Application 1: "Base and side barrier"	13
4.2.3	Application 2: "Cover barrier"	13
4.2.4	Application 3: "secondary containment of liquid waste"	14
4.3	Relevant characteristics	14
4.4	Characteristics relevant to specific conditions of use	21
4.4.1	General	21
4.4.2	Gas permeability	21
4.4.3	Burst strength and elongation	21
4.4.4	Tear strength	21
4.4.5	Friction characteristics (direct shear and inclined plane tests)	21
4.4.6	Low temperature behaviour	21
4.4.7	Weathering	22
4.4.8	Resistance to wetting and drying	22
4.4.9	Freeze-thaw cycle resistance	22
4.4.10	Resistance to root penetration	22
4.5	Release of dangerous substances	22
5	Assessment and verification of constancy of performance (AVCP)	22
5.1	General	22
5.2	Type testing	23
5.2.1	General	23
5.2.2	Test samples, testing and compliance criteria	24
5.2.3	Test reports	24
5.2.4	Shared other party results	24
5.2.5	Cascading determination of the product type results	25
5.3	Factory production control (FPC)	26
5.3.1	General	26
5.3.2	Requirements	26
5.3.3	Product specific requirements	32
5.3.4	Initial inspection of factory and of FPC	32
5.3.5	Continuous surveillance of FPC	33
5.3.6	Procedure for modifications	33
5.3.7	One-off products, pre-production products (e.g. prototypes) and products produced in very low quantity	33

Annex A (normative) Durability of geosynthetic barriers	35
A.1 General	35
A.1.1 Service Life	35
A.1.2 Type testing of durability	35
A.1.3 Mechanisms of degradation	36
A.1.4 Use of rework material	36
A.1.5 Recycled materials	36
A.2 Weathering	36
A.2.1 General	36
A.2.2 Direct tests and accelerated tests	37
A.2.3 Period of exposure	37
A.3 Products used with a service life up to 5 years	38
A.4 Other applications and service life of 25 and 50 years	38
A.4.1 General	38
A.4.2 Tests for PE type of GBR-P	39
A.4.3 Tests for FPO-type of GBR-P	40
A.4.4 Tests for EPDM type of GBR-P	41
A.4.5 Tests for GBR-P made of PVC-P	41
A.4.6 Tests for clay geosynthetic barriers (GBR-C)	42
A.5 Durability tests on GBR-P	44
A.5.1 Introduction	44
A.5.2 Microbiological resistance	44
A.5.3 Resistance to environmental stress cracking	45
A.5.4 Resistance to leaching	46
A.5.5 Resistance to oxidation/thermal ageing	48
A.6 Evaluation tests on GBR-P and GBR-C	50
A.6.1 General	50
A.6.2 Evaluation by comparison of tensile properties	50
A.6.3 Evaluation by comparison of oxidative induction time (OIT) values	51
A.6.4 Evaluation by change in mass	51
A.6.5 Evaluation by change in water permeability	51
A.7 Durability tests on GBR-B	51
A.7.1 Introduction	51
A.7.2 Microbiological resistance	52
A.7.3 Resistance to environmental stress cracking	52
A.7.4 Resistance to leaching	53
A.7.5 Resistance to oxidation/thermal ageing	54
A.7.6 Weathering resistance	54
A.8 Evaluation tests on GBR-B	55
A.8.1 General	55
A.8.2 Evaluation by comparison of tensile properties	55
A.8.3 Evaluation by change in mass	55
A.8.4 Evaluation of water permeability	55
A.8.5 Evaluation of flow resistance at elevated temperature	56
A.8.6 Evaluation of flexibility at low temperature	56
A.8.7 Evaluation of ring and ball softening point temperature	56
Annex ZA (informative) Relationship of this European Standard with Regulation (EU) No. 305/2011	57
ZA.1 Scope and relevant characteristics	57
ZA.2 System of Assessment and Verification of Constancy of Performance (AVCP)	59
ZA.3 Assignment of AVCP tasks	59
Bibliography	61